

ANTICARCOMA KLEARXYL AQUA 3



FAMILY LINE

MADERA

TRATAMIENTO CARCOMA

DESCRIPTION AND NATURE

Water-based wood protection primer. For preventive treatment against wood-eating insects (including woodworm and termites), as well as rot and blue stain fungi. For new and used wood, without direct contact with soil or constant moisture.

USAGES

In new and used woods.

Exterior, on wood subject to risk class 3. Outdoors, without direct contact with soil or constant moisture.

Outdoor/Indoor

Suitable for woodwork, doors, windows, moldings, etc.

For structures and beams, carpentry, vertical surfaces, garden furniture, etc.

We should always varnish afterwards with a wood finishing product.

PROPERTIES

Optimal applicability

No flammable

Penetrating power

Fungicide, effective against blue stain in conifers.

Low odour

Delay putrefaction. Preventive to the attack of fungi and bluish insect

Protects wood

Registered according to the European Biocidal Products Regulation: ES/MR(NA)-2023-08-00907

TECHNICAL CHARACTERISTICS

Referencia Color ANTICARCOMA KLEARXYL AQUA 3

Finish Colorless

Specific weight (1.010 ± 0.010)g/mL

Viscosity (11 ± 1) s

Solids in volume 6 ± 1

Solids in weight 7 ± 1

Aproximated performance by coat 9-10 m²/L

Dry to touch (20°C HR: 60%): 24h

Dry to repaint (20°C HR: 60%): 24h

Colours Not suitable for colouring

SURFACE PREPAIRING

New surfaces

On uncontaminated wood, usable as a preventive.

- The surface must be free of foreign products and/or residues.
- It is advisable to open the pores of the wood by sanding (40-80).
- When applying the product, the moisture content of the wood shall not exceed 18% and the surface of the wood shall be dry, clean and free of any rot at the time of treatment.
- During application and drying, the temperature must be above 5°C and the relative humidity below 80%.

Restoring and maintenance

- Remove residues of previous varnishing by mechanical means and/or sanding down to the bare wood.
- If this is not possible directly, strip beforehand.

ANTICARCOMA KLEARXYL AQUA 3

- Treat and finish as with new wood.

WAY OF USE

Application notes

1.- General:

- Wear goggles and gloves during application and handling.
- Stir the product until it is fully mixed.
- Pre-sand to ensure good penetration and evenness on the wood.
- Do not apply at high temperatures, or to surfaces in direct sunlight.
- Maintain good ventilation conditions during the drying time.
- Do not apply whilst the relative humidity is above 80%.
- Avoid contact with skin and eyes.
- Take extra care with hand and face hygiene after application, as well as before eating, drinking, etc.

Minimum consumption:

- 100 mL/m². Preventive treatment against insects (woodworms and termites) and blue stain fungi.
- 130-140 mL/m². Preventive treatment against wood-eating insects and fungi (rot).

- We should always seal the product by varnishing with finishes specifically designed for wood.

2.- In order to avoid risks to people and the environment, follow the instructions for use:

- Before using the product, read the label carefully.
- Do not apply to food or kitchen utensils.
- Do not use in the presence of people or pets.
- Adequately ventilate the room where the product is applied.
- It should not be mixed with any other chemical product.
- Do not apply the product in places where it could contaminate surface waters.
- Cover the ground with plastic sheeting during outdoor application.
- Manage waste and packaging in an appropriate manner.

3.- Specific:

- General public: Apply the product undiluted with a brush or roller.
- Specialised professional: by brushing, rolling or dipping.

Solvent for dilution and cleaning

Ready-to-use product; it should not be diluted or mixed with other products. Clean with soap and water.

Way of use	Aproximate dilution
Painting brush	0
Roller	0

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood indoor/outdoor			
MAX	Anticarcoma Klearxyl Acqua 3	Productos familia 5 Gama Madera y CREA	Productos familia 5 Gama Madera y CREA
STD	Anticarcoma Klearxyl Acqua 3		Productos familia 5 Gama Madera y CREA
varnished or painted wood outdoor/indoor			
MAX	Anticarcoma Klearxyl Acqua 3	Productos familia 5 Gama Madera y CREA	Productos familia 5 Gama Madera y CREA
STD	Anticarcoma Klearxyl Acqua 3		Productos familia 5 Gama Madera y CREA

ANTICARCOMA KLEARXYL AQUA 3



SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 18 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 2.5 L