



**FAMILY** PAREDES Y TECHOS  
**LINE** MATE PREMIUM

**DESCRIPTION AND NATURE**

High-quality vinyl plastic paint for smooth surfaces. Deep matte with excellent leveling: conceals defects such as retouching and trimming marks. High performance, coverage, whiteness, and washability. Low spatter. Mildew resistant.

**USAGES**

Indoors/Outdoors  
Walls and ceilings  
Cement mortars  
Concrete  
Brick  
Plaster  
Dripping effect  
Drywall (gypsum plasterboard): fibreboard

**PROPERTIES**

Gloss level: deep matt (according to UNE-EN 13300, at 85° reflectance < 5)  
Washability: Class 1 (according to Standard UNE-EN 13300)  
With anti-mould additive  
Opacity: Class 1 for a performance of 5 m<sup>2</sup>/litre (according to Standard UNE-EN 13300). This information may vary depending on the colour chosen.  
Gardner Washability Standard DIN 53778: 50.000 d.p

**TECHNICAL CHARACTERISTICS**

Referencia Color	OVALPROF BLANCO
Finish	Smooth extra matt
Specific weight	1,5± 0,05 kg/l
Viscosity	90 +/- 15 PO
Solids in volume	41± 1
Solids in weight	62± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,95 g/l
Aproximated performance by coat	14-16 m <sup>2</sup> /L

Dry to touch	(20°C HR:60%):1h
Dry to repaint	(20°C HR:60%):3-4h
Colours	White 103 Red Poster 205, Black 207

**SURFACE PREPAIRING**

**New surfaces**

Cement and concrete mortars:  
1. Wait until fully set (min. 30 days).  
2. Clean any efflorescence with a jet washer.  
3. Neutralize alkaline surfaces.  
4. Sand polished surfaces to create a rougher surface.  
5. Clean the surface to remove foreign products.  
6. Set crumbly substrates with Fixer Emulsion or Fijamont.  
7. Fill in defects in the substrate (see family 6)

Fecha de Alta

04-11-2008

Versión

1E - 17/07/2025

Plaster, plaster-covered brick:

1. Wait until it is completely dry (max. 20% humidity).
2. Clean the surface to remove foreign products.
3. Clean any efflorescence with a jet washer.
4. Regulate surface absorption with sealer, fixer, or a diluted coat of the same product
5. Sand polished surfaces to create a rougher surface
6. Set crumbly substrates with Fixer Emulsion or Fijamont.
7. Fill in defects in the substrate (see family 6)

Plasterboard partition walls:

1. Carry out a general sanding of the joints and putty fixing areas.
2. Then, clean them to ensure the substrate is free of dust, grease and other contaminants.
3. For application on coloured boards that tend to generate stains, apply Montoplac Stain-Resistant Sealer.

**Restoring and maintenance**

1. Completely remove old paint that is in poor condition or that is poorly-adhered.
2. Glossy surfaces should be thinned out to ensure good adhesion.
3. On painted surfaces, check that the paint is solid and well-adhered. Its condition must be assessed, in order to avoid possible incompatibilities. Dust and dirt must also be eliminated before repainting.
4. Apply filler (Plasmont) to any defects on the surface.
5. Pre-treat mouldy walls using Monto Limpia Moho.

**WAY OF USE****Application notes**

- Remove the product until perfectly homogeneous.
- Apply on clean and dry surfaces, removing dirt with soapy water. In the case of extreme dirt, it is advisable to use degreasing agents or cleaning detergents.
- Apply in accordance with requirements marked in the attached application table.
- Do not apply the product at temperatures below 5° nor on surfaces exposed to strong sunshine.
- Maintain good ventilation conditions during the drying time.
- Do not apply whilst the relative humidity is above 80%.
- For a perfect finish we recommend applying with a spray gun, but if you do use a roller it should be one designed for varnishing.
- Do not wash for the first 24 days.
- Clean tools with water immediately after use.
- Never apply it outdoors if there is an imminent risk of rain, and avoid excessively wet days.
- For spraying with Airless equipment, use 15 to 23 inch nozzles, pressure  $\approx$  150 bar.

**Solvent for dilution and cleaning**

Water

Way of use	Aproximate dilution
Painting brush	5-10%
Roller	5-10%
Air-less gun	10-20%

**SYSTEM****Procedures depending of surface type**

	Primer	Intermedium	Finish
<b>Inner painted old work in good state</b>			
<b>MAX</b>			
<b>STD</b>	Ovalprof Diluido		Ovalprof
<b>Inner painted old work in good state</b>			
<b>MAX</b>			
	Eliminar + Fijador	Ovalprof	Ovalprof
<b>STD</b>			
	Eliminar + Ovalprof Diluido		Ovalprof
<b>Project</b>			

Fecha de Alta

04-11-2008

Versión

1E - 17/07/2025

<b>MAX</b>	Fijador	Ovalprof	Ovalprof
<b>STD</b>	Ovalprof Diluido		Ovalprof

**Drywall (gypsum plasterboard)**

<b>MAX</b>	Montoplac Sellador Antimanchas	Ovalprof	Ovalprof
<b>STD</b>	Ovalprof Diluido		Ovalprof

**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE**

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

**PACKINGS**

0.75 L, 4 L, 12 L