

Fecha de Alta

06-10-2026

Versión

1 - 06/10/2026



FAMILY LINE

REVESTIMIENTOS DE FACHADAS / SISTEMAS TINTOMÉTRICOS
RUGOSOS

DESCRIPTION AND NATURE

Textured coating for the protection and decoration of exterior facades and walls. The texture helps conceal surface imperfections. It offers good durability and resistance to sunlight (UV) and rainwater. Ideal for professional application: high coverage, excellent yield, low sheen, and fast application.

USAGES

Outdoors/Indoors

Facades

Cement mortars

Porous brick

Concrete

PROPERTIES

Water vapor permeability: V2 (very breathable) (according to UNE-EN 1062-1 standard)

Dry film thickness: E5 (< 400 microns, according to standard 1062-1)

The product can be guaranteed for up to 7 years for white and 5 for COF and FE, see conditions

CE Marked (UNE-EN 1504-2)

Permeability to liquid water: W3 (maximum impermeability) (according to UNE-EN 1062-1 standard)

Carbon dioxide permeability: C1 (anti-carbonation) (according to UNE-EN 1062-1)



TECHNICAL CHARACTERISTICS

Referencia Color	MONTOKRIL RUGOSO BLANCO
Finish	Rough
Specific weight	1,75± 0,05 kg/l
Solids in volume	63± 1
Solids in weight	81± 1
VOC	Cat. c/BA 75/40 (2007/2010):5,03 g/l
Aproximated performance by coat	1,4-2 m²/L
Dry to touch	(20°C HR: 60%): 1
Dry to repaint	(20° C HR: 60%): 24h
Colours	Bases: BL, IN and TR 103 White and colors Groups C, D and E of the COF and FACHADAS ETERNAL chart. SYSTEMS tinting.

SURFACE PREPAIRING

New surfaces

Cement mortar:

1. Wait till complete drying of product (30 days minimum).
2. Remove off any efflorescences by abrasive jet and neutralize alkaline surfaces.
3. Extremely polished surfaces should be sanpapered to open pores.
4. Remove off any foreing products or remains.
5. Surfaces in bad conditions should be anchored with suitable fixer (see Family 6).

Fecha de Alta

06-10-2026

Versión

1 - 06/10/2026

6. Cover surface imperfections with Plastmont Exteriores (see Family 6 to help you choose the most suitable product to prepare surfaces).

Porous bricks:

1. Remove any cracks, holes or irregularities with Plasmont Exterior or Montó equivalent.
2. Clean the surface before painting.
3. It is advisable to apply a primer before painting due to the porosity of the brick, thus avoiding wasting paint.

Restoring and maintenance

1. On painted surfaces, check that the paint is solid and well-adhered. Its condition must be assessed, in order to avoid possible incompatibilities. Dust and dirt must also be eliminated before repainting.
2. Completely remove old paint that is in poor condition or that is poorly-adhered.
3. Treat mouldy surfaces with Monto Limpia Moho.
4. Glossy surfaces should be thinned out to ensure good adhesion.
5. Putty the surface defects with exterior filler (see the corresponding powder fillers and ready-mixed fillers in the SURFACE PREPARATION product range to make the right choice).

WAY OF USE

Application notes

- Do not apply the product at temperatures below 5°C or above 35°C, or if there is a risk of imminent rain.
- Do not apply in direct sunlight or on excessively humid days.
- Stir the product until it is completely uniform.
- It is advisable to prepare the surface with Montokril Liso in the same color to prevent excessive absorption and achieve a uniform finish.
- Finish by rolling in the same direction to achieve a uniform finish.

Solvent for dilution and cleaning

WATER

Way of use

Roller

Stucco spray gun

Aproximate dilution

0-5%

0-5%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old paintings in good condition			
MAX	Montokril Liso diluido		Montokril Rugoso
STD	Montokril Liso diluido		Montokril Rugoso
Support with mould			
MAX	Limpiar + Montó Limpia Moho	Montokril Liso diluido	Montokril Rugoso
STD	Limpiar + Montó Limpia Moho		Montokril Rugoso
Old paintings in bad state			
MAX	Eliminar + Fijamont, Emulsión Fijadora	Montokril Liso diluido	Montokril Rugoso
STD	Eliminar + Montokril Liso diluido		Montokril Rugoso
Support weak			
MAX	Fijamont, Emulsión Fijadora	Montokril Liso diluido	Montokril Rugoso
STD	Montokril Liso diluido		Montokril Rugoso

SECURITY

Fecha de Alta

06-10-2026

Versión

1 - 06/10/2026

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

4 L, 18.93 L

Canned bases 12 L