

MONTOSPRAY ELECTRODOMESTICOS



FAMILY ESMALTES
LINE SPRAY MULTISOPORTE

DESCRIPTION AND NATURE

Glossy acrylic spray enamel for quick repair of scratches and small flaws on white surfaces of household appliances such as heaters, refrigerators...

USAGES

Outdoor/Indoor
Radiators
Fridge
After correct priming

PROPERTIES

Adherence
Excellent leveling
High hiding power
Glossy finish
Withstands temperatures up to 80°C
Controlled flow rate for perfect finishes

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOSPRAY ELECTRODOMESTICOS BLANCO
Finish	Gloss
Aproximated performance by coat	Depending of product usage
Dry to touch	10min
Dry to repaint	30min
Colours	White

SURFACE PREPAIRING

New surfaces

Iron, painted metals:

- The surface must be free of foreign products and/or residues.
- The surface must be degreased, clean and dry.
- On rusty surfaces, we must remove the rust by the usual means recommended by Montó.

Restoring and maintenance

Iron and enamelled derivatives:

1. On paints in good condition, sand to open the pore, checking that the adherence is perfect.
2. On paints in bad condition, remove it by mechanical or chemical means and proceed as if it were a new surface.

WAY OF USE

Application notes

- Shake the container vigorously for about 2 minutes to homogenise its contents perfectly.
- Carry out application tests in a non-visible place.
- Protect areas that are not to be painted.
- Apply at a distance of 25-30cm from the surface in light, criss-cross strokes.
- Do not apply the product at high temperatures, or on surfaces exposed to strong sunlight.
- Maintain good ventilation conditions during the drying time.
- Do not apply while the relative humidity is above 80%.

MONTOSPRAY ELECTRODOMESTICOS

- Do not use at temperatures below 15°C.
- When finished, empty the contents of the cannula by dosing with the container upside down.
- Approximate yield per 400ml container 1-2 m2 (two cross-coats).

Solvent for dilution and cleaning

Solvent 1406-05

Way of use **Aproximate dilution**

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old paints in good condition			
MAX	Montospray Electrodomesticos		Montospray Electrodomesticos
STD			Montospray Electrodomesticos
Iron			
MAX	Montospray Electrodomesticos		Montospray Electrodomesticos
STD			Montospray Electrodomesticos

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 48 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.4 L