

CATALIZADOR MONTOEPOX AQUA SANITARIO



FAMILY PRODUCTOS PARA USO ESPECIFICO

LINE EPOXIS AL AGUA

DESCRIPTION AND NATURE

Catalyst specific to the product Montoeпок Aqua Sanitario

USAGES

Indoors
Concrete
Cement

PROPERTIES

TECHNICAL CHARACTERISTICS

Referencia Color	CATALIZADOR MONTOEPOX AQUA SANITARIO
Mixture relation	4:1
Specific weight	1,12± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage

SURFACE PREPAIRING

New surfaces

Follow the directions provided in the MONTOEPOX AQUA SANITARIO data sheet.

Restoring and maintenance

Follow the directions provided in the MONTOEPOX AQUA SANITARIO data sheet.

WAY OF USE

Application notes

Mix well with Part A, using a machine for agitation and mixing.

The product on this technical file has the indicated lifespan if it is stored in a dry place at a temperature between 5°C and 35°C in the original package.

The product can crystallise at low temperatures and, in that case, can be recovered by heating it at 50°C followed by stirring. In this way, it does not lose its characteristics and maintains its values and properties.

Solvent for dilution and cleaning

Way of use

Aproximate dilution

CATALIZADOR MONTOEPOX AQUA SANITARIO



SYSTEM

Procedures depending of surface type

Primer**Intermedium****Finish**

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 18 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1 L, 3 L