

Fecha de Alta

01-08-2006

Versión

3 - 19/01/2026



**FAMILY**  
**LINE**

**PRODUCTOS PARA USO ESPECIFICO**  
**ADITIVOS**

### DESCRIPTION AND NATURE

Matting additive to be added to solvent based products.

### USAGES

Universal flatting for solvent-based systems

### PROPERTIES

Does not alter product properties to which is added  
Additable over enamels, synthetic varnishes, Nitrocellulosic, Poliuretanic  
Allows the adjusment of desired gloss

### TECHNICAL CHARACTERISTICS

Referencia Color	CONVERPLUS MATIZADOR
Mixture relation	Se recomienda aditivar del 5 al 20% de converplus
Finish	Transparent
Specific weight	1,08± 0,05 kg/l
Solids in volume	27± 1
Solids in weight	43± 1
Aproximated performance by coat	Depending of product usage
Colours	Transparent

### SURFACE PREPAIRING

#### New surfaces

As per product to be added to.

#### Restoring and maintenance

As per product to be added to.

### WAY OF USE

#### Application notes

- Stir product until perfectly homogenized.
- Mix up with product base by spatula or agitator.
- Same as product to be added.
- Addition: 5-20% in volume.
- Apply recommended primer for every product.
- Always follow the recomend application systems indicated in corresponding product data sheet.
- In the box marked "support", we must interpret the products to be added.

#### Solvent for dilution and cleaning

Solvent 1405

**Way of use**

**Aproximate dilution**

Fecha de Alta

01-08-2006

Versión

3 - 19/01/2026

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>On usualy surfaces</b>			
<b>MAX</b>			
<b>STD</b>	Idem productos Monto a aditivar	Idem productos Monto a aditivar	Idem productos Monto a aditivar+Converplus matizador

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 18 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

0.75 L