

Fecha de Alta

08-08-2006

Versión

6 - 21/01/2026



FAMILY PAVIMENTOS

LINE COMPLEMENTOS SUELO

DESCRIPTION AND NATURE

Transparent glass spheres which, when sprinkled over Paint Specifically for Floors, adhere perfectly and reflect the light.

USAGES

Outdoors/Indoors

Floors

PROPERTIES

High stability

Inert

Do not change the drying times of the paintings when added

Reflexive additive for floor paintings (family 8)

Provides light reflection, avoiding traffic dangers

Odourless

TECHNICAL CHARACTERISTICS

Referencia Color	PIGMENTO REFLECTANTE
Finish	Gloss
Specific weight	0,97± 0,05 kg/l
Solids in volume	100± 1
Solids in weight	100± 1
Aproximated performance by coat	Depending of product usage
Colours	Translucent green colour. Do not affect the final colour of the paint they are added to. Refractive index: 1.50 to 1.52

SURFACE PREPARING

New surfaces

- Proceed as per corresponding data sheet guidelines.

Asphaltic surfaces:

- Proceed as per corresponding data sheet guidelines.

Restoring and maintenance

- Proceed as per corresponding data sheet guidelines.

WAY OF USE

Application notes

To sprinkle:

- Use the proportions indicated in the technical specifications.

- Apply over tacky, partially dry paint using suitable machinery. Brush away any excess once the end product is dry.

- If you are using a mechanical sprinkling system, given the large variety of sprinkling systems available on the market, you should check with the manufacturer that the nozzles are suitable for abrasive products (for example tungsten carbonyl). For water-based paints, rustproof materials should be used (such as stainless steel).

Fecha de Alta

08-08-2006

Versión

6 - 21/01/2026

Solvent for dilution and cleaning

Way of use	Aproximate dilution
Dusting	0
Mechanical system	

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New work			
MAX	Floor Paintings (Fam. 8)	Floor Paintings (Fam. 8)	
STD			Pigmento reflectante
Asphalt fabric			
MAX	Floor Paintings (Fam. 8)	Floor Paintings (Fam. 8)	
STD			Pigmento reflectante
Asphalt			
MAX	Floor Paintings (Fam. 8)	Floor Paintings (Fam. 8)	
STD			Pigmento reflectante

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1 Kg, 5 Kg