

Fecha de Alta

26-02-2014

Versión

14 - 08/06/2020



FAMILY

CREA

LINE

MADERA EXTERIOR

## DESCRIPTION AND NATURE

"Woodstain"-type water protector, developed with nano-particle technology, for protection of interior / exterior wood, reinforced with U.V. protection agents. Maximum colour protection.

## USAGES

Outdoors/Indoors

For maximum protection, finish in colour.

Apply a maximum of 275 +/- 25 g/m<sup>2</sup>

Recommended in high mountain and coastal areas for porous finishes, repaintable with water-based woodstain.

## PROPERTIES

- Penetration power
- Provides open pore finish
- Do not apply white media, you can amarillarlos slightly, but does not alter the properties of the product.
- Does not turn yellow
- Recommended number of coats : 2-3 coats over new wood, 1-2 coats as maintenance
- No cracking at all
- Does not form blisters
- Water steam transpirable
- Odourless when dry
- Endures brusque changes in the weather
- Flexible
- Microporous
- Highlights the wood's natural grain
- U.V. resistant
- May be used as a base when diluted, thus nourishing the wood

## TECHNICAL CHARACTERISTICS

Referencia Color	CREA LASURE MATE INCOLORO
Finish	Matt
Specific weight	0,98± 0,05 kg/l
Viscosity	18 +/- 2 PO
Solids in volume	20± 1
Solids in weight	24± 1
VOC	Cat. e/BA 150/130 (2007/2010): 4,71 g/l
Aproximated performance by coat	10-16 m <sup>2</sup> /L
Dry to touch	(20°C HR: 60%): 2-4 h. Total: 12-24 h
Dry to repaint	(20°C HR: 60%): 12-24 h
Colours	Colors: Pino, Roble, Nogal, Palisandro, Castaño, Teca, Caoba. Colourless. Montomix systems (max 5%).

## SURFACE PREPAIRING

## New surfaces

New woods.

When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment.

Fecha de Alta

26-02-2014

Versión

14 - 08/06/2020

The base must be free from foreign materials and/or waste matter.

Apply to woods with a moisture content of less than 20%.

Apply to healthy, grease-free, dust-free and dry wood.

Sand down and remove any remnants of glue from the joints and defects from mechanical process.

If the wood shows signs of ageing it must first be sanded down and any dust removed using a plane or other mechanical device.

When CREA LASURE MATE is applied in exposed conditions, following the directions for restoration and maintenance, the product has been observed to provide wood with optimal resistant protection for up to 7 years. This will always depend on the location / area, conditions and punishment to which the varnished wood is subjected.

### Restoring and maintenance

Varnished or painted wood:

- If you have varnished with open-pore wood stains such: remove foreign products, remove any loose or peeling varnish, lightly sand, remove dust from sanding and proceed as on new woods.

- If you have varnished with closed-pore varnishes, sand deeply and if necessary remove by stripping with chemical or mechanical means and proceed as on new woods.

- If you have varnished with cellulosic or polyurethane varnishes, remove by stripping with chemical or mechanical means and proceed as on new woods.

- If you have enamelled with synthetic enamels, remove by stripping by chemical or mechanical means, sand down to wood and proceed as on new woods.

- When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment.

- For items varnished with CREA LASURE MATE, to maintain their protective efficiency, it is advisable to periodically check the status / appearance of the surfaces. If there is any damage due to impacts and / or scratches, etc., we recommend cleaning and sanding the damaged area and re-varnishing it with with CREA LASURE MATE.

## WAY OF USE

### Application notes

Stir the product until perfectly blended.

Apply on clean and dry substrates.

Apply following the recommended dilutions as described in the Application Systems section.

Sand before application to ensure good penetration and smoothing on the wood.

For the first coat, it is recommended that you prime with Crea Impregnante.

Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.

Maintain good ventilation conditions while drying.

Do not apply with relative humidity over 80%.

### Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	fondo: 10-30%
Roller	10-30%
Air-less gun	30-50%
Air-mix gun	30-50%
Aerographic gun	10-30%
Low pressure turbo	10-30%

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>New /old wood indoor/outdoor</b>			
<b>MAX</b>	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Color
<b>STD</b>	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Incoloro/Color
<b>Open pore varnished wood</b>			
<b>MAX</b>	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Color
<b>STD</b>	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Incoloro/Color

Fecha de Alta

26-02-2014

Versión

14 - 08/06/2020

**Painted or varnished wood (closed pore) outdoor**

<b>MAX</b>	Exterior: Decapar + Anticarcomas Klearxyl Di	Crea Impregante Color	Crea Lasure Mate Color
<b>STD</b>	Exterior: Decapar + Anticarcomas Klearxyl Di	Crea Impregante Color	Crea Lasure Mate Incoloro/Color

**New wood/old outdoor**

<b>MAX</b>	Anticarcomas Klearxyl Di	Crea Impregante Color	Crea Lasure Mate Color
<b>STD</b>	Anticarcomas Klearxyl Di	Crea Impregante Color	Crea Lasure Mate Incoloro/Color

**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE**

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

**PACKINGS**

0.5 L, 2.5 L

**FAMILY  
LINE****DESCRIPTION AND NATURE**

"Woodstain"-type water protector, developed with nano-particle technology, for protection of interior / exterior wood, reinforced with U.V. protection agents. Maximum colour protection.

**USAGES****PROPERTIES**


- Penetration power
- Provides open pore finish
- Do not apply white media, you can amarillarlos slightly, but does not alter the properties of the product.
- Does not turn yellow
- Recommended number of coats : 2-3 coats over new wood, 1-2 coats as manteinance
- No cracking at all
- Does not form blisters

Fecha de Alta

26-02-2014

Versión

14 - 08/06/2020



- Water steam transpirable
- Odourless when dry
- Endures brusque changes in the weather
- Flexible
- Microporous
- Highlights the wood's natural grain
- U.V. resistant
- May be used as a base when diluted, thus nourishing the wood

## TECHNICAL CHARACTERISTICS

Referencia Color

Finish Matt

Specific weight 0,98± 0,05 kg/l

Viscosity 18 +/- 2 PO

Solids in volume 20± 1

Solids in weight 24± 1

VOC Cat. e/BA 150/130 (2007/2010): 4,71 g/l

Aproximated performance by coat 10-16 m<sup>2</sup>/L

Dry to touch (20°C HR: 60%): 2-4 h. Total: 12-24 h

Dry to repaint (20°C HR: 60%): 12-24 h

Colours Colors: Pino, Roble, Nogal, Palisandro, Castaño, Teca, Caoba.  
Colourless.  
Montomix systems (max 5%).

## SURFACE PREPARING

### New surfaces

New woods.

When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment. The base must be free from foreign materials and/or waste matter.

Apply to woods with a moisture content of less than 20%.

Apply to healthy, grease-free, dust-free and dry wood.

Sand down and remove any remnants of glue from the joints and defects from mechanical process.

If the wood shows signs of ageing it must first be sanded down and any dust removed using a plane or other mechanical device.

When CREA LASURE MATE is applied in exposed conditions, following the directions for restoration and maintenance, the product has been observed to provide wood with optimal resistant protection for up to 7 years. This will always depend on the location / area, conditions and punishment to which the varnished wood is subjected.

### Restoring and maintenance

Varnished or painted wood:

- If you have varnished with open-pore wood stains such: remove foreign products, remove any loose or peeling varnish, lightly sand, remove dust from sanding and proceed as on new woods.

- If you have varnished with closed-pore varnishes, sand deeply and if necessary remove by stripping with chemical or mechanical means and proceed as on new woods.

- If you have varnished with cellulosic or polyurethane varnishes, remove by stripping with chemical or mechanical means and proceed as on new woods.

- If you have enamelled with synthetic enamels, remove by stripping by chemical or mechanical means, sand down to wood and proceed as on new woods.

- When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment.

- For items varnished with CREA LASURE MATE, to maintain their protective efficiency, it is advisable to periodically check the status / appearance of the surfaces. If there is any damage due to impacts and / or scratches, etc., we recommend cleaning and sanding the damaged area and re-varnishing it with CREA LASURE MATE.

Fecha de Alta

26-02-2014

Versión

14 - 08/06/2020

## WAY OF USE

### Application notes

Stir the product until perfectly blended.

Apply on clean and dry substrates.

Apply following the recommended dilutions as described in the Application Systems section.

Sand before application to ensure good penetration and smoothing on the wood.

For the first coat, it is recommended that you prime with Crea Impregnante.

Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.

Maintain good ventilation conditions while drying.

Do not apply with relative humidity over 80%.

### Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	fondo: 10-30%
Roller	10-30%
Air-less gun	30-50%
Air-mix gun	30-50%
Aerographic gun	10-30%
Low pressure turbo	10-30%

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>New /old wood indoor/outdoor</b>			
<b>MAX</b>	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Color
<b>STD</b>	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Incoloro/Color
<b>Open pore varnished wood</b>			
<b>MAX</b>	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Color
<b>STD</b>	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Incoloro/Color
<b>Painted or varnished wood (closed pore) outdoor</b>			
<b>MAX</b>	Exterior: Decapar + Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Color
<b>STD</b>	Exterior: Decapar + Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Incoloro/Color
<b>New wood/old outdoor</b>			
<b>MAX</b>	Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Color
<b>STD</b>	Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Mate Incoloro/Color

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

771426


# CREA LASURE MATE

Fecha de Alta

26-02-2014

Versión

14 - 08/06/2020



## NOTE

## PACKINGS

0.5 L, 2.5 L