

# CREA BARNIZ INTERIOR MATE



**FAMILY** CREA / SISTEMAS TINTOMÉTRICOS

**LINE** MADERA INTERIOR

## DESCRIPTION AND NATURE

Water-based varnish, made with latest technology acrylic emulsions, for varnishing, protecting and decorating all types of interior wood.

## USAGES

Indoors  
 Exterior with protection.  
 Ideal for general carpentry.  
 Solid Wood and Veneer  
 Suitable for furniture and doors  
 Cement  
 Plaster  
 Concrete  
 Brick  
 Apply a maximum of 275 +/- 25 g/m<sup>2</sup>  
 Use over clean woods

## PROPERTIES

Good adhesion  
 Good resistance  
 Non Yellowing  
 Flexible  
 Microporous  
 Highlights the wood's natural grain  
 Excellent covering  
 Odourless  
 Superior waterproofing

## TECHNICAL CHARACTERISTICS

Referencia Color	CREA BARNIZ INTERIOR MATE INCOLORO
Finish	Matt
Specific weight	1 ± 0,05 kg/l
Viscosity	13 +/- 2 PO
Solids in volume	23 ± 1
Solids in weight	28 ± 1
VOC	Cat. e/BA 150/130 (2007/2010): 4,80 g/l
Aproximated performance by coat	10-15 m <sup>2</sup> /L
Dry to touch	(20°C HR: 60%): 1-3h
Dry to repaint	(20°C HR: 60%): 16-24h
Colours	Colorless, Oak, Walnut, Chestnut, Teak, Mahogany.

## SURFACE PREPARING

### New surfaces

New wood:

- The support must be free of any remaining product or residue.
- Apply in which the moisture content is less than 20%.

# CREA BARNIZ INTERIOR MATE

- Apply on healthy, well degreased, dust-free and dry wood.
- Sand and remove any remaining bonding glue.
- If the wood shows signs of aging, sand in advance, then remove the dust with a brush.

## Restoring and maintenance

Varnished or painted wood:

- If the wood has been varnished with open pore stains: remove the remains of old products, remove badly adhered or in poor condition, sand lightly, remove dust after sanding and then proceed as in new wood.
- If the wood has been varnished with closed-pore varnishes or another similar product, sand well and, if necessary, remove the product by stripping or using mechanical means, then proceed as in new wood.
- If the wood has been varnished with cellulose or polyurethane varnishes, remove them by stripping or mechanical means, then proceed as in new wood.
- If the wood has been lacquered with synthetic lacquers, remove them by pickling or using mechanical means, sand to the wood, then proceed as in new wood.

## WAY OF USE

### Application notes

- Stir the product until it is perfectly homogenized.
- Apply on clean and dry substrates.
- Apply following the dilutions recommended in the Application Systems section.
- Pre-sand to guarantee a good penetration and leveling on the wood.
- In the first hand, it is advisable to prime preferably with Crea Impregnante.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- Maintain good ventilation conditions during the drying time.
- Do not apply with relative humidity higher than 80%

### Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Air-mix gun	0-10%
Aerographic gun	5-10%
Brush, Roller	0-20%

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>Indoor wood (closed pore)</b>			
<b>MAX</b>	Crea Impregnante	Crea Barniz Interior Brillo/Satinado/Mate	Crea Barniz Interior Brillo/Satinado/Mate
<b>STD</b>	Crea Barniz Interior Brillo/Satinado/Mate		Crea Barniz Interior Brillo/Satinado/Mate

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

# CREA BARNIZ INTERIOR MATE

## NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

0.5 L, 2.5 L



## FAMILY LINE

### DESCRIPTION AND NATURE

Water-based varnish, made with latest technology acrylic emulsions, for varnishing, protecting and decorating all types of interior wood.

## USAGES

## PROPERTIES

- Good adhesion
- Good resistance
- Non Yellowing
- Flexible
- Microporous
- Highlights the wood's natural grain
- Excellent covering
- Odourless
- Superior waterproofing

## TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1 ± 0,05 kg/l
Viscosity	13 +/- 2 PO
Solids in volume	23 ± 1
Solids in weight	28 ± 1

VOC Cat. e/BA 150/130 (2007/2010): 4,80 g/l

Aproximated performance by coat 10-15 m<sup>2</sup>/L

Dry to touch	(20°C HR: 60%): 1-3h
Dry to repaint	(20°C HR: 60%): 16-24h
Colours	Colorless, Oak, Walnut, Chestnut, Teak, Mahogany.

## SURFACE PREPAIRING

## New surfaces

New wood:

- The support must be free of any remaining product or residue.
- Apply in which the moisture content is less than 20%.
- Apply on healthy, well degreased, dust-free and dry wood.
- Sand and remove any remaining bonding glue.
- If the wood shows signs of aging, sand in advance, then remove the dust with a brush.

## Restoring and maintenance

Varnished or painted wood:

- If the wood has been varnished with open pore stains: remove the remains of old products, remove badly adhered or in poor condition, sand lightly, remove dust after sanding and then proceed as in new wood.
- If the wood has been varnished with closed-pore varnishes or another similar product, sand well and, if necessary, remove the product by stripping or using mechanical means, then proceed as in new wood.
- If the wood has been varnished with cellulose or polyurethane varnishes, remove them by stripping or mechanical means, then proceed as in new wood.
- If the wood has been lacquered with synthetic lacquers, remove them by pickling or using mechanical means, sand to the wood, then proceed as in new wood.

## WAY OF USE

### Application notes

- Stir the product until it is perfectly homogenized.
- Apply on clean and dry substrates.
- Apply following the dilutions recommended in the Application Systems section.
- Pre-sand to guarantee a good penetration and leveling on the wood.
- In the first hand, it is advisable to prime preferably with Crea Impregnante.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- Maintain good ventilation conditions during the drying time.
- Do not apply with relative humidity higher than 80%

### Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Air-mix gun	0-10%
Aerographic gun	5-10%
Brush, Roller	0-20%

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>Indoor wood (closed pore)</b>			
<b>MAX</b>	Crea Impregnante	Crea Barniz Interior Brillo/Satinado/Mate	Crea Barniz Interior Brillo/Satinado/Mate
<b>STD</b>	Crea Barniz Interior Brillo/Satinado/Mate		Crea Barniz Interior Brillo/Satinado/Mate

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

771437


Fecha de Alta

27-02-2014

Versión

8 - 28/10/2024

# CREA BARNIZ INTERIOR MATE



Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

## PACKINGS

0.5 L, 2.5 L