

Fecha de Alta

27-06-2017

Versión

1E - 28/10/2024



FAMILY CREA / SISTEMAS TINTOMÉTRICOS

LINE MADERA JARDIN

DESCRIPTION AND NATURE

Suitable protector for decks and exterior woods floors. Exterior / Interior. Waterproof, UV and weather resistant. With transparent iron oxides that lengthen the natural appearance of the wood. Penetrates and protects wood while maintaining its natural appearance. Easy application and maintenance. Low odor.

USAGES

Outdoors/Indoors

Suitable for woodwork, doors, windows, moldings, etc.

Suitable for parquet and wooden floors

Wood previously primed with Crea Impregnante Color

Restore wood degraded by atmospheric agents

Water repellent

For maximum protection, finish in colour.

Wood decking and floors

Apply a maximum of 110 +/- 20 g/m2 per coat.

Use over clean woods

PROPERTIES

Penetration power

- Colour range

For maximum protection outdoors, give it coloured

Water resistant

Good adhesion

Environmentally friendly.

Non Yellowing

Outdoor resistance

Easily applicable

High performance

Reinforced with U.V. filter

TECHNICAL CHARACTERISTICS

Referencia Color	CREA TARIMAS BASE TR
Finish	Matt
Specific weight	0,99± 0,05 kg/l
Viscosity	20 +/- 3 SG
Solids in volume	24± 1
Solids in weight	26± 1
VOC	Cat. e/BA 150/130 (2007/2010): 11,44 g/l
Aproximated performance by coat	8-12 m ² /L
Dry to touch	60min
Dry to repaint	12-14h
Colours	Chestnut, Iroco, Ipe.

SURFACE PREPAIRING

Fecha de Alta

27-06-2017

Versión

1E - 28/10/2024

New surfaces

New woods:

- The support must be free of foreign products and / or residues.
- Apply on healthy, well degreased, dust-free and dry woods.
- In each step of painting, apply to wood with a moisture content of less than 20%, and an H.R. less than 80%.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- New tropical woods should be cleaned with CREA wood cleaner, to remove greases and resins.
- Outside, protect the wood with KLEARXYL DI Anticarcomas from fungal and insect attack.
- Essential sanding with grain 40 - 60.
- It is highly recommended to prime with CREA Colored Impregnante.
- Give one or two coats of CREA Pallets, without exceeding the maximum recommended thickness.
- The wood on the outside is photo-degraded after a few months, losing its initial appearance.
- The choice of a color from the beginning, guarantees a similar appearance for a longer time, being able to recover this color in subsequent maintenance with another finishing coat, and delaying the photo-degradation of the support.
- It allows to lengthen the maintenance intervals.
- Maintenance intervals are difficult to determine. Generally, by checking the status every six months, the next maintenance can be established. Maximum observed durability of 24 months.

Restoring and maintenance

Varnished or painted woods:

- If they have been varnished or oiled, and the condition of the wood allows it, remove areas that are poorly adhered or in poor condition, sand, remove the dust resulting from sanding.
- If it is suspected that they have been oiled, they must be removed with CREA wood cleaner so that the wood is permeable to water.
- In all cases, with the sanding, of coarse grain, it is necessary to reach the wood in good condition, which will have a different color than the first layer.
- Continue as in the case of new woods.
- Review the status every six months, establishing the next maintenance.

Wood grayed by atmospheric agents:

- Make sure that under the surface there is wood in good condition. The presence of cracks indicates that the wood has lost much of its elasticity. Maintenance should be more frequent.
- Assess the condition of the wood, sometimes the loss of a large part of elasticity, recommends removing the flooring.
- Continue as in the case of varnished or painted woods.
- Review the status every six months, establishing the next maintenance.

WAY OF USE**Application notes**

- On Crea Tarimas or Crea Colored Impregnant, you can apply Crea Tarimas non-slip Colorless (See TDS).
- Stir the product until it is perfectly homogenized.
- Apply on clean and dry substrates.
- Pre-sand to guarantee a good penetration and leveling on the wood.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- Apply on wood with a moisture content of less than 20%
- Maintain good ventilation conditions during the drying time.
- Do not apply with relative humidity higher than 80%.
- Do not wet, at least for 48 hours after the application of the last coat.
- Inspect at the end of each campaign.
- Continuous maintenance is the best way to ensure a well preserved wood. Recoveries after long periods with low maintenance usually require shorter maintenance intervals.
- The starting state of the wood to be painted is key in obtaining good results. As the wood loses elasticity and density, maintenance should be more frequent.

* Good practices:

- Avoid, as far as possible, watering the flooring in conditions of high temperature, the rapid contractions of the flooring, generate an unnecessarily faster degradation of it.
- Cleaning with high pressure water is not recommended.

Solvent for dilution and cleaning

Water

Fecha de Alta

27-06-2017

Versión

1E - 28/10/2024

Way of use	Aproximate dilution
Painting brush	Al uso
Spray gun	Al uso
Roller	Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood indoor/outdoor			
MAX	Anticarcomas Klearxyl Di	Crea Tarimas Coloreado	Crea Tarimas Coloreado
STD	Anticarcomas Klearxyl Di	Crea Impregnante coloreado.	Crea Tarimas Coloreado
varnished or painted wood outdoor/indoor			
MAX	Decapar+ Anticarcomas Klearxyl Di	Crea Tarimas Coloreado	Crea Tarimas Coloreado
STD	Decapar+ Anticarcomas Klearxyl Di	Crea Impregnante Coloreado	Crea Tarimas
Maintenance system			
MAX	Examinar periódicamente.	Crea Impregnante Coloreado.	Crea Tarimas Coloreado
STD	Examinar periódicamente.		Crea Tarimas Coloreado

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adecuate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.5 L, 2.5 L



FAMILY LINE

DESCRIPTION AND NATURE


Suitable protector for decks and exterior woods floors. Exterior / Interior. Waterproof, UV and weather resistant. With transparent iron oxides that lengthen the natural appearance of the wood. Penetrates and protects wood while maintaining its natural appearance. Easy application and maintenance. Low odor.

Fecha de Alta

27-06-2017

Versión

1E - 28/10/2024



USAGES

PROPERTIES

Penetration power

- Colour range

For maximum protection outdoors, give it coloured

Water resistant

Good adhesion

Environmentally friendly.

Non Yellowing

Outdoor resistance

Easily applicable

High performance

Reinforced with U.V. filter

TECHNICAL CHARACTERISTICS

Referencia Color

Finish

Matt

Specific weight

0,99± 0,05 kg/l

Viscosity

20 +/- 3 SG

Solids in volume

24± 1

Solids in weight

26± 1

VOC

Cat. e/BA 150/130 (2007/2010): 11,44 g/l

Aproximated performance by coat

8-12 m²/L

Dry to touch

60min

Dry to repaint

12-14h

Colours

Chestnut, Iroco, Ipe.

SURFACE PREPARING

New surfaces

New woods:

- The support must be free of foreign products and / or residues.
- Apply on healthy, well degreased, dust-free and dry woods.
- In each step of painting, apply to wood with a moisture content of less than 20%, and an H.R. less than 80%.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- New tropical woods should be cleaned with CREA wood cleaner, to remove greases and resins.
- Outside, protect the wood with KLEARXYL DI Anticarcomas from fungal and insect attack.
- Essential sanding with grain 40 - 60.
- It is highly recommended to prime with CREA Colored Impregnante.
- Give one or two coats of CREA Pallets, without exceeding the maximum recommended thickness.
- The wood on the outside is photo-degraded after a few months, losing its initial appearance.
- The choice of a color from the beginning, guarantees a similar appearance for a longer time, being able to recover this color in subsequent maintenance with another finishing coat, and delaying the photo-degradation of the support.
- It allows to lengthen the maintenance intervals.
- Maintenance intervals are difficult to determine. Generally, by checking the status every six months, the next maintenance can be established. Maximum observed durability of 24 months.

Restoring and maintenance

Varnished or painted woods:

Fecha de Alta

27-06-2017

Versión

1E - 28/10/2024

- If they have been varnished or oiled, and the condition of the wood allows it, remove areas that are poorly adhered or in poor condition, sand, remove the dust resulting from sanding.
- If it is suspected that they have been oiled, they must be removed with CREA wood cleaner so that the wood is permeable to water.
- In all cases, with the sanding, of coarse grain, it is necessary to reach the wood in good condition, which will have a different color than the first layer.
- Continue as in the case of new woods.
- Review the status every six months, establishing the next maintenance.

Wood grayed by atmospheric agents:

- Make sure that under the surface there is wood in good condition. The presence of cracks indicates that the wood has lost much of its elasticity. Maintenance should be more frequent.
- Assess the condition of the wood, sometimes the loss of a large part of elasticity, recommends removing the flooring.
- Continue as in the case of varnished or painted woods.
- Review the status every six months, establishing the next maintenance.

WAY OF USE

Application notes

- On Crea Tarimas or Crea Colored Impregnant, you can apply Crea Tarimas non-slip Colorless (See TDS).
- Stir the product until it is perfectly homogenized.
- Apply on clean and dry substrates.
- Pre-sand to guarantee a good penetration and leveling on the wood.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- Apply on wood with a moisture content of less than 20%
- Maintain good ventilation conditions during the drying time.
- Do not apply with relative humidity higher than 80%.
- Do not wet, at least for 48 hours after the application of the last coat.
- Inspect at the end of each campaign.
- Continuous maintenance is the best way to ensure a well preserved wood. Recoveries after long periods with low maintenance usually require shorter maintenance intervals.
- The starting state of the wood to be painted is key in obtaining good results. As the wood loses elasticity and density, maintenance should be more frequent.

* Good practices:

- Avoid, as far as possible, watering the flooring in conditions of high temperature, the rapid contractions of the flooring, generate an unnecessarily faster degradation of it.
- Cleaning with high pressure water is not recommended.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	Al uso
Spray gun	Al uso
Roller	Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood indoor/outdoor			
MAX	Anticarcomas Klearxyl Di	Crea Tarimas Coloreado	Crea Tarimas Coloreado
STD	Anticarcomas Klearxyl Di	Crea Impregnante coloreado.	Crea Tarimas Coloreado
varnished or painted wood outdoor/indoor			
MAX	Decapar+ Anticarcomas Klearxyl Di	Crea Tarimas Coloreado	Crea Tarimas Coloreado
STD	Decapar+ Anticarcomas Klearxyl Di	Crea Impregnante Coloreado	Crea Tarimas

Maintenance system

Fecha de Alta

27-06-2017

Versión

1E - 28/10/2024



MAX	Examinar periódicamente.	Crea Impregnante Coloreado.	Crea Tarimas Coloreado
STD	Examinar periódicamente.		Crea Tarimas Coloreado

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

0.5 L, 2.5 L