

Fecha de Alta

26-06-2007

Versión

4 - 13/03/2015



FAMILY TRATAMIENTOS DE LA MADERA

LINE ACEITES PROTECTORES (RESTAUR.)

DESCRIPTION AND NATURE

High quality linseed oil with drying additives, for use as a wood protector, impregnating agent and sealer

USAGES

Outdoors/Indoors

Wood

PROPERTIES

Elasticity
 Penetration power
 Sun & rain protective
 To avoid putrefaction
 Non-plumbing dryers addition
 - Highlights shade

TECHNICAL CHARACTERISTICS

Referencia Color	ACEITE DE LINAZA
Finish	Transparent
Specific weight	0,86± 0,05 kg/l
Viscosity	41 +/- 15 SG
Solids in volume	1± 1
Solids in weight	63± 1
Aproximated performance by coat	8-12 m ² /L
Dry to touch	(20°C HR 60%): 24-48 h
Dry to repaint	(20°C HR 60%): mín 24 h
Colours	Candy. Tintable with Montotinte max 5%.

SURFACE PREPAIRING

New surfaces

- New wood:
- The base must be free from foreign materials and/or waste matter.
- Apply to wood with a moisture content of less than 20%.
- Apply to healthy wood that is dry and free from grease and dust.
- Sand down and remove any remains of glue in joints and defects from mechanical processes.
- If the wood shows signs of aging must be pre-sanded and removing dust by brushing or other mechanical means.
- Applied using a paint gun; the most highly recommended is "Sistema Airless".

Restoring and maintenance

- Varnished or painted woods:
1. If the wood has been varnished with Montoxyl Color, remove foreign products, remove any varnish that is loose or in poor condition, gently sand down, remove the sanding dust and proceed as with new wood.
 2. If varnished with closed pore varnish such as Barniz Sintético Universal Mate (Code: 1350), Satinado or Brillante, Barniz Veleró, Barniz Alta Montaña or similar, remove by stripping with Quitamont where there are blisters, raised edges or cracks. If the surface is in good condition, gently sand, remove the dust from sanding and proceed as for new wood.
 3. If previously varnished with cellulose or polyurethane varnish, remove by stripping with Quitamont Universal (Code: 3510) or mechanical means, and proceed as for new wood.
 4. If enamelled with synthetic enamel (Montosintetic Code: 2020, 2024), Marisma (Code: 2010, 2014), Luxatín (Code: 2028)

Fecha de Alta

26-06-2007

Versión

4 - 13/03/2015

or similar, remove by stripping with Quitamont Universal (Code: 3510) or mechanical means, and proceed as for new wood.

WAY OF USE

Application Notes

- Stir the product until perfectly blended.
- Apply as supplied.
- Do not apply the product at high temperatures nor to surfaces exposed to strong insolation.
- Ensure good ventilation while product is drying.
- Do not apply with relative humidity above 80%.

Solvent for dilution and cleaning

Solvent 1401,1413

Way of use	Aproximate dilution
Painting brush	0-10%
Roller	0-10%
Air-less gun	10-20%
Air-mix gun	10-20%
Aerographic gun	10-20%
Low pressure turbo	10-20%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Wood			
MAX	Aceite de linaza diluido	Aceite de linaza diluido	Aceite de linaza diluido
STD	Aceite de linaza diluido	Aceite de linaza diluido	Aceite de linaza diluido

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adecuate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1 L, 5 L