

MONTOXYL LASURE ACQUA ACABADO PIGMENTADO



FAMILY TRATAMIENTOS DE LA MADERA / SISTEMAS TINTOMÉTRICOS
LINE PROTECTORES AL AGUA (P. A.)

DESCRIPTION AND NATURE

Wood matt protection treatment, microporous, for the protection of woods exteriors. Elastic and excellent adhesion. Easy to apply, no smell. Paintable in tinting system.

USAGES

Outdoors/Indoors
Wood
Specially recommended for mountain and coastal areas

PROPERTIES

Does not turn yellow
No cracking at all
Does not form blisters
- Filling capacity
Water steam transpirable
Odourless when dry
- Endures brusque changes in the weather
- Flexible
- Microporous
- Highlights the wood's natural grain
- U.V. resistant
- May be used as a base when diluted, thus nourishing the wood
- Delays rotting
Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOXYL LASURE ACQ.ACAB.PIGMENT.BLANCO
Finish	Semi-matt
Specific weight	1,24± 0,05 kg/l
Viscosity	40 +/- 5 PO
Solids in volume	34± 1
Solids in weight	48± 1
VOC	Cat. e/BA 150/130 (2007/2010): 130,00 g/l
Aproximated performance by coat	8-12 m ² /L

Dry to touch	(20°C HR: 60%): 2-4 h.
Dry to repaint	(20°C HR: 60%): 12-24 h
Colours	Tinting system, charts RAL and NCS AFNOR NFT 36005 Familia I clase 7b2.

SURFACE PREPAIRING

New surfaces

New wood
-Surface should be free of any foreign products or remains.
-Apply on wood with less than 20% moisture content.
-Apply on wood in good condition, dry and free of grease and dust.
-Sandpaper and eliminate any remains in joints and mechanical faults.

MONTOXYL LASURE ACQUA ACABADO PIGMENTADO

-Old wood should be previously sandpapered and dust-free.

Restoring and maintenance

Painted or varnished surfaces:

-If they have been varnished with Montoxyl Color (ref. 1300), remove off foreign remains, or areas in bad condition, sandpaper slightly, brush any resulting dust and proceed as per new wood.

-If the have been varnished with close pore varnishes such as Barniz Sintetico Universal Mat (ref. 1350), Satinado (Ref. 1360 or Brillante (Ref. 1370), Barniz Veleró (ref. 1380), Barniz Alta Montaña (ref. 1385) or similar, apply a stripping product such as Quitamont Universal (ref. 3510) or use a mechanical system if any blisters or cracks have arisen and proceed as per new wood. If surfaces are in good condition, sandpaper slightly, brush any resulting dust and proceed as per new wood.

-If they have been varnished with cellulose or polyutherane based varnished, apply a stripping product such as Quitamont Universal (ref. 3510) or use a mechanical system and proceed as per new wood.

-If they have been painted with synthetic enamels (such as Montosintetic ref. 2020, 2024), Marisma (ref. 2010, 2014), Luxatin (ref. 2028) or similar, apply a stripping product such as Quitamont Universal (ref. 3510) or use a mechanical system and proceed as per new wood.

WAY OF USE

Application Notes

-Stir product completely.

-Only apply on clean and dry surfaces.

-Dilute product according to application system recommendations.

-Surface should be sandpapered previously to ensure good product penetration and wood levelling.

-Keep room well ventilated while product is drying.

-Do not apply at high temperatures or on overheated surfaces exposed to sunshine.

-Do not apply when moisture content is over 80%.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	0-15%
Roller	0-15%
Spray gun	10-25%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New /old wood indoor/outdoor			
MAX	Lasure acqua o Montoxyl Fondo Color	Lasure acqua (ext: color)	Lasure acqua
STD	Lasure acqua o Montoxyl Fondo Color		Lasure acqua
Open pore varnished wood			
MAX	Lasure acqua o Montoxyl Fondo (ext: Color)	Lasure acqua (ext: color)	Lasure acqua
STD	Lasure acqua o Montoxyl Fondo (ext: Color)		Lasure acqua
Closed pore wood			
MAX	Decapar+Fondo lasure acqua o Montoxyl fondo	Lasure Acqua	Lasure Acqua
STD	Decapar+Fondo lasure acqua o Montoxyl fondo		Lasure Acqua

SECURITY

MONTOXYL LASURE ACQUA ACABADO PIGMENTADO



Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 4 L