

ACRIPOL METALIZADO + CATALIZADOR



FAMILY ESMALTES / SISTEMAS TINTOMÉTRICOS

LINE POLIURETANOS (2 COMPONENTES)

DESCRIPTION AND NATURE

Two-component metallic aliphatic acrylic polyurethane enamel.

USAGES

Outdoors/Indoors
Iron
Galvanized iron
Plastic
Fibre
Wood,

PROPERTIES

- Strongness
- Elasticity
- Resistance to friction and hits
- Good adhesion
- Does not turn yellow
- Strong resistance to the atmospherical factors
- Easy application
- Does not form blisters
- Perfect leveling

TECHNICAL CHARACTERISTICS

Referencia Color	ACRIPOL METALIZADO+CAT. GRIS PLATA
Mixture relation	4 Acripol : 1 Catalizador EN VOLUMEN
Finish	Gloss
Specific weight	1,03± 0,05 kg/l
Viscosity	120 +/- 30 SG
Solids in volume	46± 1
Solids in weight	56± 1
VOC	Cat. j/BD 550/500 (2007/2010):500,00 g/l
Aproximated performance by coat	8-14 m ² /L
Dry to touch	(20°C HR: 60%): 30-60 min, Furnace: 30 min
Dry to repaint	12-24 h
Colours	Base: Silver Grey 800, colours from the metallic colour chart

SURFACE PREPARING

New surfaces

-Enamelled iron and derivatives:

1. On paintwork which is in good condition, sand down to open the pore, checking that the adhesion is perfect.
2. On paintwork in bad condition, remove paint by mechanical or chemical means and proceed as with new bases.

Varnished or painted wood:

1. If the wood has been varnished with Montoxyl colour (code1300): Remove foreign products, remove any loose or peeling varnish, lightly sand, remove dust from sanding and proceed as with new woods.
2. If they have been varnished, strip down using Quitamont or by mechanical means and proceed as with new wood.

ACRIPOL METALIZADO + CATALIZADOR

Plaster work (plaster, cement or derivatives):

1. On paintwork which is in good condition, sand down to open the pore, checking that the adhesion is perfect.
2. On paintwork which is in poor condition or vulnerable to attack by the product, remove by mechanical or chemical means and proceed as with new plaster/cement work.

Restoring and maintenance

-Enamelled iron and derivatives:

1. On paintwork which is in good condition, sand down to open the pore, checking that the adhesion is perfect.
2. On paintwork in bad condition, remove paint by mechanical or chemical means and proceed as with new bases.

Varnished or painted wood:

1. If the wood has been varnished with Montoxyl colour (code1300): Remove foreign products, remove any loose or peeling varnish, lightly sand, remove dust from sanding and proceed as with new woods.
2. If they have been varnished, strip down using Quitamont or by mechanical means and proceed as with new wood.

Plaster work (plaster, cement or derivatives):

1. On paintwork which is in good condition, sand down to open the pore, checking that the adhesion is perfect.
2. On paintwork which is in poor condition or vulnerable to attack by the product, remove by mechanical or chemical means and proceed as with new plaster/cement work.

WAY OF USE

Application notes

Stir the product until perfectly blended.

Apply to clean, dry substrates, remove any waste matter using degreasers or detergents and clean water.

The desired metallic finish can be achieved with one or two coats.

Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.

Maintain good ventilation conditions while drying.

Do not apply with relative moisture above 80%.

Given the broad spectrum of bases, for direct applications on problematic surfaces, it is recommended that you first carry out adhesion tests. If false adhesion is detected, prime as indicated in the attached table.

As a preventive measure, prime using the products indicated in the table attached. On tiles and ceramic surfaces, carry out adhesion tests.

Solvent for dilution and cleaning

1410

Way of use

Air-less gun

Air-mix gun

Aerographic gun

Aproximate dilution

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Wood			
MAX	Montopol fondo		Acipol
STD	Montopol fondo		Acipol
Iron, steel,			
MAX	Impripol, Impriepox	Impripol, Impriepox	Acipol
STD	Impripol, Impriepox	Impripol, Impriepox	Acipol
Work indoors / outdoors			
MAX	Barniz acipol	Acipol	Acipol
STD	Acipol	Acipol	Acipol
Tiles, Ceramic Material			

502058

Fecha de Alta

18-10-2007

Versión

7 - 20/07/2020

ACRIPOL METALIZADO + CATALIZADOR

MONTÓ
profesional

MAX Imprimol

Acropol

Acropol

STD Acropol

Acropol

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 12 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 4 L