



## FAMILY LINE

PREPARACIONES, FONDOS E IMPR.

AL USO (MASILLAS)

## DESCRIPTION AND NATURE

Plastic putty in paste form. Ready to use. Outstanding application, whiteness .

## USAGES

Outdoors/Indoors

Cement

Plaster

Plaster

Wood

Cement

Concrete

Plaster

It can be used for filling and levelling surface imperfections, it helps crack filling and seal off joints

## PROPERTIES

Strongness

Non-flammable

Penetration power

Without product loosings, remainings can be used immediately

It avoids losing time for mixing, because product is ready to use

Minimum decrease

Good adhesion

Penetration power

recommended thickness per coat : 1,5 mm

Good applicability

Drying fast

Good adhesion

## TECHNICAL CHARACTERISTICS

Referencia Color PLASMONT AL USO MULTIUSO

Finish Matt

Specific weight  $1,82 \pm 0,05$  kg/l

Solids in volume  $59 \pm 1$

Solids in weight  $79 \pm 1$

Aproximated performance by coat Depending of product usage

Dry to touch (20°C HR: 60%): 1-3 h. Sandpaper: 16 h

Dry to repaint 24 h

Colours White

## SURFACE PREPAIRING

### New surfaces

Plaster and cement mortar:

-Apply suitable fixer before puttying (see family 6) Emulsion Fijadora, Fijamont, Fijalite.

-Test PLASMONT AL USO suitability on surface.

-Wait till complete drying of product (30 days).

-Remove off any efflorescences and neutralize alkaline surfaces.

-Extremely polished surfaces should be sandpapered to open pores.

Fecha de Alta

15-07-2008

Versión

3 - 03/03/2016

- Remove off any foreing products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT AL USO as recommended under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer (see family 6) before puttying.
- Recommended maximum thickness per coat should always be observed.

Wood:

- Test PLASMONT ACABADOS suitability on surface.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreing products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT ACABADOS as recommended under Application Systems and Application points.
- Recommended maximum thickness per coat should always be observed.
- Only apply on wood in good condition, with no trace of resine exudates, dry and free of dust and grease, with less than 20% moisture level.
- Old wood should be previously sandpapered and dust-free.

## Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpàpering or any other mechanical systems.

Test adherence level and treat as per new surfaces.

## WAY OF USE

### Application Notes

- Very absorbent surfaces should be previously moistened.
- Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.
- Use only recommended clean and dust-free tools as per Application Systems.

### Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Large Pallette	uso
Pallette / spatula	uso
Pallette	uso

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>New work</b>			
<b>MAX</b>			
<b>STD</b>	Plasmont al Uso	Fijador(Emulsión Fijadora Fijamont)	Montoplástica, Ovaldine, Montonature, Montosintétic, Luxatín
<b>wood indoor</b>			
<b>MAX</b>			
<b>STD</b>	Plasmont al uso	Fondos e imprimaciones para madera (familia 4)	Ovaldine, Montonature, montosintétic, Luxatín, Acabados pigmentados para madera

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Fecha de Alta

15-07-2008

Versión

3 - 03/03/2016

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

0.5 Kg, 1 Kg, 5 Kg, 20 Kg



## FAMILY LINE

## DESCRIPTION AND NATURE

Plastic putty in paste form. Ready to use. Outstanding application, whiteness .

## USAGES

## PROPERTIES

Strongness  
Non-flammable  
Penetration power  
Without product lossings, remainings can be used immediately  
It avoids losing time for mixing, because product is ready to use  
Minimum decrease  
Good adhesion  
Penetration power  
recommended thickness per coat : 1,5 mm  
Good applicability  
Drying fast  
Good adhesion

## TECHNICAL CHARACTERISTICS

Referencia Color

Finish Matt

Specific weight 1,82± 0,05 kg/l

Solids in volume 59± 1

Solids in weight 79± 1

Aproximated performance by coat Depending of product usage

Dry to touch (20°C HR: 60%): 1-3 h. Sandpaper: 16 h

Dry to repaint 24 h

Fecha de Alta

15-07-2008

Versión

3 - 03/03/2016

Colours

White

**SURFACE PREPAIRING****New surfaces**

Plaster and cement mortar:

- Apply suitable fixer before puttying (see family 6) Emulsion Fijadora, Fijamont, Fijalite.
- Test PLASMONT AL USO suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT AL USO as recommended under Application Systems and Application points.
- For extremely damaged surfaces, use suitable fixer (see family 6) before puttying.
- Recommended maximum thickness per coat should always be observed.

Wood:

- Test PLASMONT ACABADOS suitability on surface.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT ACABADOS as recommended under Application Systems and Application points.
- Recommended maximum thickness per coat should always be observed.
- Only apply on wood in good condition, with no trace of resin exudates, dry and free of dust and grease, with less than 20% moisture level.
- Old wood should be previously sandpapered and dust-free.

**Restoring and maintenance**

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

Test adherence level and treat as per new surfaces.

**WAY OF USE****Application Notes**

- Very absorbent surfaces should be previously moistened.
- Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.
- Use only recommended clean and dust-free tools as per Application Systems.

**Solvent for dilution and cleaning**

Water

Way of use	Aproximate dilution
Large Pallette	uso
Pallette / spatula	uso
Pallette	uso

**SYSTEM****Procedures depending of surface type**

	Primer	Intermedium	Finish
<b>New work</b>			
<b>MAX</b>			
<b>STD</b>	Plasmont al Uso	Fijador(Emulsión Fijadora Fijamont)	Montoplástica, Ovaldine, Montonature, Montosintético, Luxatin
<b>wood indoor</b>			

**MAX**

Fecha de Alta

15-07-2008

Versión

3 - 03/03/2016

**STD** Plasmont al usoFondos e imprimaciones para madera  
(familia 4)Ovaldine, Montonature,  
montosintético, Luxatín, Acabados  
pigmentados para madera**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in drain. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE****PACKINGS**

0.5 Kg, 1 Kg, 5 Kg, 20 Kg