

Fecha de Alta

04-07-2007

Versión

2 - 09/05/2016


FAMILY PREPARACIONES, FONDOS E IMPR.

LINE AL USO (MASILLAS)

DESCRIPTION AND NATURE

Synthetic levelling putty in paste form. Ready to use. Recommended for wood and walls preparation work. Easy sanding. Solvent-based

USAGES

Indoors
Indoors
Cement
Plaster
Plaster
Wood
Supports with porosity

PROPERTIES

Strongness
Elasticity
Fast sanding
Good as sealer
Excellent touch
Good adhesion
Good adhesion

TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT OLEOSINTETICO
Finish	Matt
Minimum recommended thickness	1 mm
Aproximated performance by coat	Depending of product usage

Dry to touch	(20°C HR:60%): 8h
Dry to repaint	(20°C HR:60%): 16h
Colours	White

SURFACE PREPAIRING
New surfaces

Plaster and cement mortar:

- Test PLASMONT OLEOSINTETICO suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT OLEOSINTETICO as recommended under Application Systems and Application points.
- Recommended maximum thickness per coat should always be observed.

Wood:

- Test PLASMONT OLEOSINTETICO suitability on surface.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT OLEOSINTETICO as recommended under Application Systems and Application points.
- Recommended maximum thickness per coat should always be observed.

Fecha de Alta

04-07-2007

Versión

2 - 09/05/2016

-Only apply on wood in good condition, with no trace of resin exudates, dry and free of dust and grease, with less than 20% moisture level.

-Old wood should be previously sanded and dust-free.

Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

Test adherence level and treat as per new surfaces.

WAY OF USE

Application Notes

-Use only recommended clean and dust-free tools as per Application Systems.

-Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.

Solvent for dilution and cleaning

Way of use	Aproximate dilution
Pallette / spatula	al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old/New interior Wood			
MAX			
STD	Plasmont Oleosintético	Plasmont Oleosintético	Acropol, Montonature, Montosintético, Luxatín
Metal decoration			
MAX			
STD	Familia 6 Imprimaciones, Hierro y metales	Plasmont Oleosintético	Acropol, Montonature, Montosintético, Luxatín
Exterior new/old buildings			
MAX			
STD	Plasmont Oleosintético	Fijador (Emulsión Fijadora)	montoplástica, Ovaldine, Montonature, Montosintético, Luxatín
Interior new/old buildings			
MAX			
STD	Plasmont Oleosintético	Fijador (Emulsión Fijadora)	montoplástica, Ovaldine, Montonature, Montosintético, Luxatín

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Fecha de Alta

04-07-2007

Versión

2 - 09/05/2016

NOTE

Maximum recommended storage time : 36 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1 Kg, 5 Kg



FAMILY LINE

DESCRIPTION AND NATURE

Synthetic levelling putty in paste form. Ready to use. Recommended for wood and walls preparation work. Easy sanding. Solvent-based

USAGES

PROPERTIES

Strongness
Elasticity
Fast sanding
Good as sealer
Excellent touch
Good adhesion
Good adhesion

TECHNICAL CHARACTERISTICS

Referencia Color

Finish Matt

Minimum recommended thickness 1 mm

Aproximated performance by coat Depending of product usage

Dry to touch (20°C HR: 60%): 8h

Dry to repaint (20°C HR: 60%): 16h

Colours White

SURFACE PREPAIRING

New surfaces

Plaster and cement mortar:

- Test PLASMONT OLEOSINTETICO suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.

Fecha de Alta

04-07-2007

Versión

2 - 09/05/2016

-Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT OLEOSINTETICO as recommended under Application Systems and Application points.

-Recommended maximum thickness per coat should always be observed.

Wood:

-Test PLASMONT OLEOSINTETICO suitability on surface.

-Extremely polished surfaces should be sandpapered to open pores.

-Remove off any foreign products or remains.

-Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply PLASMONT OLEOSINTETICO as recommended under Application Systems and Application points.

-Recommended maximum thickness per coat should always be observed.

-Only apply on wood in good condition, with no trace of resin exudates, dry and free of dust and grease, with less than 20% moisture level.

-Old wood should be previously sandpapered and dust-free.

Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.

Test adherence level and treat as per new surfaces.

WAY OF USE

Application Notes

-Use only recommended clean and dust-free tools as per Application Systems.

-Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.

Solvent for dilution and cleaning

Way of use

Pallete / spatula

Aproximate dilution

al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Old/New interior Wood			
MAX			
STD	Plasmont Oleosintético	Plasmont Oleosintético	Acropol, Montonature, Montosintético, Luxatín
Metal decoration			
MAX			
STD	Familia 6 Imprimaciones, Hierro y metales	Plasmont Oleosintético	Acropol, Montonature, Montosintético, Luxatín
Exterior new/old buildings			
MAX			
STD	Plasmont Oleosintético	Fijador (Emulsión Fijadora)	montoplástica, Ovaldine, Montonature, Montosintético, Luxatín
Interior new/old buildings			
MAX			
STD	Plasmont Oleosintético	Fijador (Emulsión Fijadora)	montoplástica, Ovaldine, Montonature, Montosintético, Luxatín

SECURITY

502330


PLASMONT OLEOSINTETICO

Fecha de Alta

04-07-2007

Versión

2 - 09/05/2016



Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

1 Kg, 5 Kg