



**FAMILY** PREPARACIONES, FONDOS E IMPR.

**LINE** AL USO (MASILLAS)

## DESCRIPTION AND NATURE

Ready to use filler for smoothing textured surfaces, can be applied in thick layers. Specially suitable for smoothing textured surfaces.

## USAGES

Indoors  
Indoors  
Plaster  
Plaster  
Cement  
Concrete  
Plaster

## PROPERTIES

Adherence  
Applicability  
Non-flammable  
Fast drying  
High thickness coats  
It fix very good over Matt Water Paintings  
Easy sandable  
Minimum decrease  
Long open time  
maximum recommended thickness : 7mm

## TECHNICAL CHARACTERISTICS

Referencia Color	PLASMONT AL USO RENOVACION
Finish	Matt
Specific weight	1,71 ± 0,05 kg/l
Solids in volume	52 ± 1
Solids in weight	74 ± 1

Aproximated performance by coat Depending of product usage

Dry to touch	(20°C HR: 60%): Task: 4-5h. Sanding: 24h
Dry to repaint	(20°C HR: 60%): 24-48 h
Colours	White

## SURFACE PREPAIRING

### New surfaces

Cement / plaster mortar:

Check the suitability of the filler for the surface.

Wait until it has completely set (at least 30 days)

Clean any efflorescence off the base, and neutralise alkaline surfaces.

Sand excessively polished surfaces to increase porosity.

Clean surface removing other products and/or residues.

Open up any cracks or fissures until you reach a sound base, brush off the dust, and apply the filler or plaster as shown in the Application Systems and Application sections.

- Do not apply coats that are thicker than the recommended maximum.

- On extremely crumbly surfaces, before applying the filler, fix it with the appropriate fixative: Fijalite, Fijamont, Fijadora

Fecha de Alta

09-08-2006

Versión

4 - 15/10/2015

Emulsion Paint

### Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpàpering or any other mechanical systems.

Check the adhesion and treat as for new BASES.

## WAY OF USE

### Application Notes

Use clean and rust-free tools detailed in the Application System.

Anchor adequately.

We usually recommend coats of between 5-7 mm at most.

Three or more coats can be applied to a thickness of up to 15 mm.

Repaint following the indicated period of time. Given that this depends on the levels of humidity, temperature and thickness of the coating, when the sandpaper does not clog, this indicates that the product is ready for repainting.

Suitable finishing products: Ovaldine, Montoplástica, Montonature, Esmalte Montosintético, Luxatín and Alta Decoración products.

### Solvent for dilution and cleaning

Water

#### Way of use

Large Pallette

Pallette / spatula

#### Aproximate dilution

400ml de agua por kg

400ml de agua por kg

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>New work</b>			
<b>MAX</b>	Emulsión fijadora, Fijamont, Fijalite	Plasmont renovación	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoración.
<b>STD</b>	Plasmont renovación	Emulsión fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoración.
<b>Plasterboard</b>			
<b>MAX</b>	Plasmont renovación	Plasmont renovación	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoración.
<b>STD</b>	Plasmont renovación	Fijador (Emulsón fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoración.

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

# PLASMONT AL USO RENOVACION

## NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

5 Kg, 20 Kg



## FAMILY LINE

### DESCRIPTION AND NATURE

Ready to use filler for smoothing textured surfaces, can be applied in thick layers. Specially suitable for smoothing textured surfaces.

## USAGES

## PROPERTIES

Adherence  
 Applicability  
 Non-flammable  
 Fast drying  
 High thickness coats  
 It fix very good over Matt Water Paintings  
 Easy sandable  
 Minimum decrease  
 Long open time  
 maximum recommended thickness : 7mm

## TECHNICAL CHARACTERISTICS

Referencia Color	
Finish	Matt
Specific weight	1,71 ± 0,05 kg/l
Solids in volume	52 ± 1
Solids in weight	74 ± 1
Aproximated performance by coat	Depending of product usage
Dry to touch	(20°C HR: 60%): Task: 4-5h. Sanding: 24h
Dry to repaint	(20°C HR: 60%): 24-48 h
Colours	White

## SURFACE PREPAIRING

## New surfaces

Cement / plaster mortar:

Check the suitability of the filler for the surface.

Wait until it has completely set (at least 30 days)

Clean any efflorescence off the base, and neutralise alkaline surfaces.

Sand excessively polished surfaces to increase porosity.

Clean surface removing other products and/or residues.

Open up any cracks or fissures until you reach a sound base, brush off the dust, and apply the filler or plaster as shown in the Application Systems and Application sections.

- Do not apply coats that are thicker than the recommended maximum.

- On extremely crumbly surfaces, before applying the filler, fix it with the appropriate fixative: Fijalite, Fijamont, Fijadora Emulsion Paint

## Restoring and maintenance

Remove off any remains or chipping of product or any other foreign product. Open pore by sandpæping or any other mechanical systems.

Check the adhesion and treat as for new BASES.

## WAY OF USE

### Application Notes

Use clean and rust-free tools detailed in the Application System.

Anchor adequately.

We usually recommend coats of between 5-7 mm at most.

Three or more coats can be applied to a thickness of up to 15 mm.

Repaint following the indicated period of time. Given that this depends on the levels of humidity, temperature and thickness of the coating, when the sandpaper does not clog, this indicates that the product is ready for repainting.

Suitable finishing products: Ovaldine, Montoplástica, Montonature, Esmalte Montosintético, Luxatín and Alta Decoración products.

### Solvent for dilution and cleaning

Water

#### Way of use

Large Pallette

Pallette / spatula

#### Aproximate dilution

400ml de agua por kg

400ml de agua por kg

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>New work</b>			
<b>MAX</b>	Emulsión fijadora, Fijamont, Fijalite	Plasmont renovación	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoración.
<b>STD</b>	Plasmont renovación	Emulsión fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintetic, Luxatín, Alta decoración.
<b>Plasterboard</b>			
<b>MAX</b>	Plasmont renovación	Plasmont renovación	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoración.
<b>STD</b>	Plasmont renovación	Fijador (Emulsón fijadora, Fijamont	Montoplástica, Montonature, Ovaldine, Montosintético, Luxatín, Alta decoración.

## SECURITY

502331


Fecha de Alta

09-08-2006

Versión

4 - 15/10/2015

# PLASMONT AL USO RENOVACION



Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

## PACKINGS

5 Kg, 20 Kg