

# MONTOKRIL L-500 SUPERBLANCO



**FAMILY** REVESTIMIENTOS DE FACHADAS

**LINE** REVESTIMIENTOS LISOS

## DESCRIPTION AND NATURE

Water paint for facades, it provides very appreciated finish by his slight harshness, with great adhesion. Raincoat and transpirable. To emphasize its extraordinary whiteness and covering.

## USAGES

Outdoors/Indoors

Cement

Facades

Cement mortars

Lime Mortars

Primer for the Muros Medit. Capri application

## PROPERTIES

Surface leveling

Waterproof

Good coverage

Good adhesion

Strong resistance to the atmospherical factors

Does not spread flame

5 year warranty after issue of the official MONTÓ certificate

Prevents micro-fissures formed by surface movements

Good yield

No cracking at all

Water steam transpirable

Excellent whiteness

## TECHNICAL CHARACTERISTICS

Referencia Color MONTOKRIL L-500 SUPERBLANCO

Finish Smooth slightly sanded

Specific weight 1,65± 0,05 kg/l

Viscosity 155 +/- 15 PO

Solids in volume 46± 1

Solids in weight 68± 1

VOC Cat. c/BA 75/40 (2007/2010):0,60 g/l

Aproximated performance by coat 6-9 m<sup>2</sup>/L

Dry to touch (20°C HR: 60%): 30 min-1h. Washing: 25-30 days

Dry to repaint (20°C HR: 60%): 4-6 h

Colours White

## SURFACE PREPARING

### New surfaces

Cement mortars:

1. Hope until forged total (mín 30 days).
2. Clean the possible eflorescencias with abrasive spurt.
3. Neutralize the alkaline surfaces.
4. Polished surfaces: to sandpaper ( open pore).

Fecha de Alta

23-04-2008

Versión

7 - 04/03/2020

5. Clean all strange product on support.
6. Fix the weak supports by means of suitable fixing primer (to see family 6).
7. Fill the defects of the support (to see family 6).

Plaster:

1. Wait until very dry (máx, 20% of humidity).
2. Clean all strange product on support.
3. Clean the possible eflorescencias with abrasive spurt.
4. Regulate the absorptions of the support with primer or a diluted coat of same product.
5. In polished surfaces, to sandpaper (to open pore).
6. Fix the weak supports with suitable fixing primer (to see family 6).
7. Fill the defects of the support (to see family 6)

### Restoring and maintenance

1. Eliminate totally old paintings in badly state or badly adhered.
2. The shining surfaces must be clarified, to make sure a good adhesion.
3. In painted supports you must verify the solidity and anchorage of the painting, to diagnose his nature to avoid possible incompatibilidades and eliminate the dust and the dirt before being paints.
4. Fill with plaste the defects of the support (to see in family 6).
5. Deal with Montolimp the supports with mould.

## WAY OF USE

### Application Notes

- Shake the product until perfect homogenization.
- Dilute the product based on the porosity and state of the support in undercoat.
- To end one or more coats slightly diluted until the total covering of the support.
- Not apply the product to inferior temperatures to 5° C nor in exposed surfaces to a strong insolation.
- Avoid the excessively humid days and the application to high temperatures of the support.

### Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	10-20%
Roller	10-20%
Air-less gun	10-30%
Air-mix gun	10-30%
Aerographic gun	10-30%
Low pressure turbo	10-30%

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>Support with mould</b>			
<b>MAX</b>	Montolimp	Montokril liso L-500 Superblanco+Montoplas	Montokril liso L-500 Superblanco+Montoplas
<b>STD</b>	Montolimp		Montokril liso L-500 Superblanco+Montoplas
<b>New work</b>			
<b>MAX</b>	Fijamot, Emulsión Fijadora	Montokril liso L-500 Superblanco	Montokril liso L-500 Superblanco
<b>STD</b>	Montokril liso L-500 Superblanco diluido		Montokril liso L-500 Superblanco
<b>Old paintings in bad state</b>			
<b>MAX</b>	Eliminar+Fijamot, Emulsión Fijadora	Montokril liso L-500 Superblanco	Montokril liso L-500 Superblanco
<b>STD</b>	Eliminar+Montokril liso L-500 Superblanco diluido		Montokril liso L-500 Superblanco

Fecha de Alta

23-04-2008

Versión

7 - 04/03/2020

## Old painting in good state

<b>MAX</b>	Montokril liso L-500 Superblanco diluido	Montokril liso L-500 Superblanco	Montokril liso L-500 Superblanco
<b>STD</b>	Montokril liso L-500 Superblanco diluido		Montokril liso L-500 Superblanco

## Wood

<b>MAX</b>	Selladora Sellalux o Selladora Acqua Blanca	Montokril liso L-500 Superblanco	Montokril liso L-500 Superblanco
<b>STD</b>	Selladora Sellalux o Selladora Acqua Blanca		Montokril liso L-500 Superblanco

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

## NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

4 L, 12 L, 15 L