

Fecha de Alta

18-02-2008

Versión

6 - 11/03/2020



**FAMILY** ANTIHUMEDAD E IMPERMEABILIZAC.  
**LINE** IMPERMEABILIZACION VERTICAL

### DESCRIPTION AND NATURE

Water based transparent varnish, specially formulated for the protection of porous and absorbent surfaces.

It does not alter practically the aspect of the support. You must avoid excesses of product that forms film.

### USAGES

Outdoors/Indoors

Brick

Stone

Exposed brickwork

Fibre-cement

Cement mortars

### PROPERTIES

Waterproof

Does not alter support tone once dry

Do protect the varnished surfaces from atmospherical factors

To fix the dusty surfaces

Porosity regulator

Does not spread flame

### TECHNICAL CHARACTERISTICS

|                                 |                                       |
|---------------------------------|---------------------------------------|
| Referencia Color                | UNO BARNIZ LADRILLO                   |
| Finish                          | Transparent                           |
| Specific weight                 | 0,98± 0,05 kg/l                       |
| Viscosity                       | 30 +/- 10 SG                          |
| Solids in volume                | 18± 1                                 |
| Solids in weight                | 19± 1                                 |
| VOC                             | Cat. c/BA 75/40 (2007/2010):38,84 g/l |
| Aproximated performance by coat | 9-15 m <sup>2</sup> /L                |
| Dry to touch                    | (20°C HR 60%): 30 min -1 h            |
| Dry to repaint                  | (20°C HR 60%): 8h                     |
| Colours                         | Colourless                            |

### SURFACE PREPAIRING

#### New surfaces

- 1 -Remove off any efflorescences, remains or foreign products by abrasive jet and neutralize alkaline surfaces.
- 2 -Extremely polished surfaces should be sanpapered to open pores.
- 3 -Cover surface imperfections with suitable plaster.
- 4 -Mildewed surfaces should be treated with Montolimp.

#### Restoring and maintenance

- 1.This product should only be applied on surfaces free of any paint trace and with open porous.
- 2.For old surfaces that comply with these requirements, proceed as per new surfaces.

Fecha de Alta

18-02-2008

Versión

6 - 11/03/2020

## WAY OF USE

### Application Notes

-Shake product until perfectly homogenized.

-Dilute the product from 100 to 25% in water. The bigger the porous, is the less thinning needs. Excess of product may cause glossy areas.

-This product should not be applied at temperatures below 5° or any surfaces which have been in the sun.

### Solvent for dilution and cleaning

Water

#### Way of use

Painting brush

Roller

Air-less gun

Air-mix gun

Aerographic gun

Low pressure turbo

#### Aproximate dilution

1:1 en agua primera mano/4 barniz:1agua siguientes

1:1 en agua primera mano/4 barniz:1agua siguientes

1:1 en agua primera mano/4 barniz:1agua siguientes

1:1 en agua primera mano/4 barniz:1agua siguientes

1:1 en agua primera mano/4 barniz:1agua siguientes

1:1 en agua primera mano/4 barniz:1agua siguientes

## SYSTEM

### Procedures depending of surface type

|                                                            | Primer                      | Intermedium         | Finish                          |
|------------------------------------------------------------|-----------------------------|---------------------|---------------------------------|
| <b>Support with mould</b>                                  |                             |                     |                                 |
| <b>MAX</b>                                                 | Montolimp                   | Uno Barniz Ladrillo | Uno Barniz Ladrillo + Montoplás |
| <b>STD</b>                                                 | Montolimp                   |                     | Uno Barniz Ladrillo + Montoplás |
| <b>Old paintings in bad state</b>                          |                             |                     |                                 |
| <b>MAX</b>                                                 | Eliminar antiguas pinturas  | Uno Barniz Ladrillo | Uno Barniz Ladrillo             |
| <b>STD</b>                                                 | Eliminar antiguas pinturas  |                     | Uno Barniz Ladrillo             |
| <b>Brickwork</b>                                           |                             |                     |                                 |
| <b>MAX</b>                                                 | Uno Barniz Ladrillo         |                     | Uno Barniz Ladrillo             |
| <b>STD</b>                                                 | Uno Barniz Ladrillo         |                     | Uno Barniz Ladrillo             |
| <b>Support weak</b>                                        |                             |                     |                                 |
| <b>MAX</b>                                                 | Fijamont, Emulsión Fijadora | Uno Barniz Ladrillo | Uno Barniz Ladrillo             |
| <b>STD</b>                                                 | Fijamont, Emulsión Fijadora |                     | Uno Barniz Ladrillo             |
| <b>Masonry mortar</b>                                      |                             |                     |                                 |
| <b>MAX</b>                                                 | Fijamont, Emulsión Fijadora | Uno Barniz Ladrillo | Uno Barniz Ladrillo             |
| <b>STD</b>                                                 | Uno Barniz Ladrillo         |                     | Uno Barniz Ladrillo             |
| <b>Artificial stone, bricks , and porous roofing tiles</b> |                             |                     |                                 |
| <b>MAX</b>                                                 | Uno Barniz Ladrillo         |                     | Uno Barniz Ladrillo             |
| <b>STD</b>                                                 | Uno Barniz Ladrillo         |                     | Uno Barniz Ladrillo             |

## SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Fecha de Alta

18-02-2008

Versión

6 - 11/03/2020

## NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

0.75 L, 4 L, 12 L