

Fecha de Alta

21-06-2006

Versión

4 - 30/05/2019


FAMILY PRODUCTOS PARA USO ESPECIFICO

LINE COLORANTES LIQUIDOS

DESCRIPTION AND NATURE

Liquid colourings compatible with the majority of water-based and solvent-based paints for obtaining pastel and intermediate tones. For interior and exterior use depending on the colour.

USAGES

Pastel or intermediate tones in solvent paints based on dispersions type: Acrylic, Acrylic-Styrenic, vinyl, homopolymers
 Pastel or intermediate shades in water-based paints by standard dispersions of the following kinds: Acrylics, Acrylic-Styrene, Vinyls, Homopolymers
 Compatible with most paints in aqueous medium or solvent

PROPERTIES

Solids high contents

Easily additable

Its tinting and resistance depends on Pigmentary concentration in paint volume, for which different products will be obtained from different densities on final resistance colours

TECHNICAL CHARACTERISTICS

Referencia Color	MONTOTINTE UNIVERSAL NEGRO
Specific weight	1,09± 0,05 kg/l
Solids in volume	9± 1
Solids in weight	15± 1
Minimum recommended thickness	5% sobre pintura
Aproximated performance by coat	Depending of product usage
Colours	Exterior colours: Black-101, Ochre-162, Rust Red-152, Beige-164 Interior colours: Yellow-131, Mid-Yellow-132, Bright Red-150, Blue-186, Green-124, Olive-123

SURFACE PREPARING
New surfaces

-Proceed in the way indicated by the paints to be dyed.

Restoring and maintenance

-Proceed in the way indicated by the paints to be dyed.

WAY OF USE
Application Notes

-Homogenise the product by shaking it lightly.

-Slowly add it to the paint.

-Add it to the paint in question and mechanically shake it or stir according to the indication in the technical characteristics of the paint.

-For large quantities of the product, add the colouring first to a small amount of paint and later pour in the rest.

-Despite its low tendency to flocculate, you should conduct a test, especially if you are using black Montotinte Universal. If you notice any type of flocculation, consult with our Customer Services (SAC) department, which will provide you with the relevant solutions for each case.

Fecha de Alta

21-06-2006

Versión

4 - 30/05/2019

Solvent for dilution and cleaning

Universal Water or Solvent 1405, according to the paint, whether water or solvent-based

Way of use **Aproximate dilution****SYSTEM****Procedures depending of surface type**

Primer

Intermedium

Finish

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 18 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.05 L, 0.2 L, 1 L