

Fecha de Alta

22-08-2007

Versión

2 - 02/03/2020



FAMILY DISOLVENTES

LINE DISOLVENTES

### DESCRIPTION AND NATURE

Isoparaffin solvents, very faint odor and free from aromatic, specially designed for Tixoway, enamels and varnishes odorless.

### USAGES

Cleanliness of tools in the recommended products

Regulator application viscosity in paints Tixoway Antihumos and Tixoway Antihumedad

### PROPERTIES

Applicability

Odourless

Suitable evaporation velocity, obtaining a perfect balance between external and internal drying

Delays product initial drying time, but not the final, for which permits an excellent leveling

Does not harm final product properties if the proportions are the adequate

Ideal to dilute enamels and synthetic conventional varnishes

Poor dilution capability

### TECHNICAL CHARACTERISTICS

Referencia Color DISOLVENTE SIN OLOR 1412

Finish Transparent

Specific weight 0,73± 0,05 kg/l

Solids in volume 0± 1

Solids in weight 0± 1

Approximated performance by coat Depending of product usage

### SURFACE PREPARING

#### New surfaces

Proceed as indicated on the paint on which this product is recommended.

#### Restoring and maintenance

Proceed as indicated on the paint on which this product is recommended.

### WAY OF USE

#### Application Notes

-As a viscosity regulator:

-Add to paint or varnish, in the proportion set out in the specifications of the product to be diluted.

-Stir the above mixture slowly with a spatula until perfectly blended.

-As a solvent for cleaning tools:

-Clean the tools immediately after use, until the varnish or paint has completely disappeared.

-Then clean with soapy water and dry immediately after washing.

#### Solvent for dilution and cleaning

Fecha de Alta

22-08-2007

Versión

2 - 02/03/2020

Way of use

Aproximate dilution

**SYSTEM**

Procedures depending of surface type

Primer

Intermedium

Finish

**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE**

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

**PACKINGS**

0.75 L, 1 L, 5 L