

Fecha de Alta

01-04-2008

Versión

11 - 30/07/2015



FAMILY SISTEMAS TINTOMÉTRICOS

LINE PINTURAS PLASTICAS

## DESCRIPTION AND NATURE

Vinyl emulsion paint. For interior and exterior surfaces. Gives excellent whiteness and glossy finish.

## USAGES

Outdoors/Indoors

Plaster

Plaster

Dripping effect

Cement mortars

## PROPERTIES

Adherence

Does not turn yellow

Applicability

Gloss

Do not crack

Makes a film

Flexible

Do not blister

Washability

Levelling

Strong resistance to the atmospherical factors

Does not spread flame

High performance

Odourless when dry

Euroclasses certification as per norm UNE EN 13501-1:07:A2-s1-d0

AFNOR T. 30.003 - FAMILIA I CLASE 7b2 - CLASSIFIED

Specific tinting control, opacity, contrast relation and flocculation, to warrantee the correct system use.

This controls permit to reproduce faithfully the colours with tintometric machines.

- Gloss rating (85°): 85 ± 5 %

## TECHNICAL CHARACTERISTICS

Referencia Color	OVALDINE SATINADO BASE IN
Finish	Satin
Specific weight	1,17 ± 0,05 kg/l
Viscosity	138 +/- 10 PO
Solids in volume	41 ± 1
Solids in weight	52 ± 1
VOC	Cat. b/BA 150/100 (2007/2010): 100,00 g/l
Aproximated performance by coat	14-16 m <sup>2</sup> /L
Dry to touch	The yield given is approximate and may vary depending on the colour to be achieved on each base (20°C HR: 60%): 1 h. Lavado 25-30 days
Dry to repaint	(20°C HR: 60%): 3-4 h
Colours	BL, TR, IN. Colors of the System Dyed Tintométrico universal Montotinte máx 5%

## SURFACE PREPAIRING

Fecha de Alta

01-04-2008

Versión

11 - 30/07/2015

**New surfaces**

Cement mortar:

- Wait till complete drying of product (30 days minimum).
  - Remove off any efflorescences by abrasive jet and neutralize alkaline surfaces.
  - Extremely polished surfaces should be sanpapered to open pores.
  - Remove off any foreing products or remains.
  - Use Emulsión Fijadora like primer to prevent "sheen".
  - Cover surface imperfections with Plastmont Exteriores (See Family 6 to help you choose the most suitable product to prepare surfaces).
- Plaster:
- Wait till complete drying of product (20% max. Moisture level).
  - Remove off any foreign product or product remains.
  - Remove off any efflorescences.
  - Use a sealant or matt paste to regulate surface absorption.
  - Extremely polished surfaces should be sandpapered to open pore.
  - Very damaged surfaces should be fixed with suitable product (See Family 6.)
  - Cover surface imperfections with plaster or putty (See Family 6 to help you choose the most suitable product to prepare surfaces).
  - Use Emulsión Fijadora like primer to prevent "sheen".
  - Mildewed surfaces should be treated with Montolimp.

**Restoring and maintenance**

1. Remove off old paint completely.
2. Brilliant surfaces should be matted to ensure good adherence.
3. Check paint type and anchoring in painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
4. Cover surface imperfections with suitable putty of plaster (See Family 6 to help you choose the most suitable product to prepare surfaces).
5. Use Emulsión Fijadora like primer to prevent "sheen".
6. Mildewed surfaces should be treated with Montolimp.

**WAY OF USE****Application Notes**

Shake product until perfectly homogenized.

This product should be dilluted depending on surface conditon and porosity level.

Finish with one or more coats slightly dilluted until surface is totally covered.

Do not apply product at temperatures below 5°C or any surfaces which have been exposed to sunshine.

**Solvent for dilution and cleaning**

Water

Way of use	Aproximate dilution
Painting brush	10-20%
Roller	10-20%
Air-less gun	10-30%
Air-mix gun	10-30%
Aerographic gun	10-30%
Low preasure turbo	10-30%

**SYSTEM****Procedures depending of surface type**

	Primer	Intermedium	Finish
<b>Support with mould</b>			
<b>MAX</b>	Imprimación Fijadora		
<b>STD</b>	Montolimp + Imprimación Fijadora	Ovaldine Satinado + Montolimp	Ovaldine Satinado + Montoplas
<b>New work</b>			
<b>MAX</b>	Fijamont, Emulsión Fijadora	Ovaldine Satinado	Ovaldine Satinado

Fecha de Alta

01-04-2008

Versión

11 - 30/07/2015

<b>STD</b>	Ovaldine Satinado diluido	Ovaldine Satinado
------------	---------------------------	-------------------

**New wood indoor/outdoor**

<b>MAX</b>	Selladora Sellalux	Ovaldine Satinado	Ovaldine Satinado
------------	--------------------	-------------------	-------------------

<b>STD</b>	Ovaldine Satinado diluido	Ovaldine Satinado
------------	---------------------------	-------------------

**Old paintings in bad state**

<b>MAX</b>	Eliminar + Fijamont, Emulsión Fijadora	Ovaldine Satinado	Ovaldine Satinado
------------	--	-------------------	-------------------

<b>STD</b>	Eliminar + Imprimación Fijadora + Ovaldine Satinado diluido	Ovaldine Satinado
------------	---	-------------------

**Old painting in good state**

<b>MAX</b>	Imprimación Fijadora	Ovaldine Satinado	Ovaldine Satinado
------------	----------------------	-------------------	-------------------

<b>STD</b>	Imprimación Fijadora + Ovaldine Satinado diluido	Ovaldine Satinado
------------	--	-------------------

**Iron, steel,**

<b>MAX</b>	Imprimación férrea Familia 6	Ovaldine Satinado	Ovaldine Satinado
------------	------------------------------	-------------------	-------------------

<b>STD</b>	Ecoprimer	Ovaldine Satinado
------------	-----------	-------------------

**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

**NOTE**

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

**PACKINGS**

0.75 L, 4 L, 12 L