

Fecha de Alta

09-08-2006

Versión

6 - 26/03/2015



FAMILY SISTEMAS TINTOMÉTRICOS / SISTEMAS TINTOMÉTRICOS
LINE PINTURAS PLASTICAS

DESCRIPTION AND NATURE

Vinyl emulsion paint. Gives a superb satin gloss finish. Ideal for interior and exterior surfaces. Excellent quality-price ratio.

USAGES

Outdoors/Indoors

Cement

Plaster

Iron

Wood

Dripping effect

PROPERTIES

Does not turn yellow

Applicability

Gloss

Do not crack

Coverage

Makes a film

Flexible

Waterproof

Washability

Strong resistance to the atmospherical factors

Does not spread flame

Whiteness

Odourless when dry

AFNOR T. 30.003 - FAMILIA I CLASE 7b2 - CLASSIFIED

Specific tinting control, opacity, contrast relation and flocluaqtion, to warantee the correct system use.

TECHNICAL CHARACTERISTCS

Referencia Color	IBERSAT BASE BL
Finish	Satin
Specific weight	1,19± 0,05 kg/l
Viscosity	119 +/- 10 PO
Solids in volume	38± 1
Solids in weight	50± 1
VOC	Cat. b/BA 150/100 (2007/2010): 100,00 g/l
Aproximated performance by coat	11-13 m ² /L

Dry to touch	(20°C HR: 60%): 1h.Washing: 25-30 días
--------------	--

Dry to repaint	(20°C HR: 60%): 3-4 h
----------------	-----------------------

Colours	BL, TR, IN. Colours Tintometric System. Tinted with Montotinte max. 5%
---------	---

SURFACE PREPAIRING

New surfaces

Cement mortar:

Fecha de Alta

09-08-2006

Versión

6 - 26/03/2015

- Wait till complete drying of product (30 days minimum).
- Remove off any efflorescences by abrasive jet and neutralize alkaline surfaces.
- Extremely polished surfaces should be sanpapered to open pores.
- Remove off any foreing products or remains.
- Use Emulsión Fijadora like primer to prevent "sheen".
- Cover surface imperfections with Plastmont Exteriores (See Family 6 to help you choose the most suitable product to prepare surfaces).
- Plaster:
- Wait till complete drying of product (20% max. Moisture level).
- Remove off any foreign product or product remains.
- Remove off any efflorescences.
- Use a sealant or matt paste to regulate surface absorption.
- Extremely polished surfaces should be sandpapered to open pore.
- Very damaged surfaces should be fixed with suitable product (See Family 6.)
- Cover surface imperfections with plaster or putty (See Family 6 to help you choose the most suitable product to prepare surfaces).
- Use Emulsión Fijadora like primer to prevent "sheen".
- Mildewed surfaces should be treated with Montolimp.

Restoring and maintenance

1. Remove off old paint completely.
2. Brilliant surfaces should be matted to ensure good adherence.
3. Check paint type and anchoring in painted surfaces to avoid incompatibilities. Remove off any dust or dirt before painting.
4. Cover surface imperfections with suitable putty of plaster (See Family 6 to help you choose the most suitable product to prepare surfaces).
5. Use Emulsión Fijadora like primer to prevent "sheen".
6. Mildewed surfaces should be treated with Montolimp.

WAY OF USE

Application Notes

Shake product until perfectly homogenized.

This product should be dilluted depending on surface conditon and porosity level.

Finish with one or more coats slightly dilluted until surface is totally covered.

Do not apply product at temperatures below 5°C or any surfaces which have been exposed to sunshine.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	10-20%
Roller	10-20%
Air-less gun	10-30%
Air-mix gun	10-30%
Aerographic gun	10-30%
Low preasure turbo	10-30%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Support with mould			
MAX			
STD	Montolimp + Imprimación Fijadora		Ibersat industrial+Montoplas
New work			
MAX	Fijamont, Emulsión Fijadora		
STD	Imprimación Fijadora + Ibersat industrial diluido	Ibersat industrial	Ibersat industrial

Fecha de Alta

09-08-2006

Versión

6 - 26/03/2015

New wood indoor/outdoor**MAX** Selladora 2340, 2350**STD** Ibersat industrial diluido Ibersat industrial Ibersat industrial**Old paintings in bad state****MAX****STD** Imprimación Fijadora + Ibersat industrial diluido Ibersat industrial Ibersat industrial**Old painting in good state****MAX****STD** Imprimación Fijadora + Ibersat industrial diluido Ibersat industrial**Iron, Steel****MAX** Imprimaciones férreas de la familia 6**STD** Ecoprimer Ibersat industrial**SECURITY**

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.75 L, 4 L, 12 L