

CREA LASURE ULTRA SATINADO



FAMILY CREA

LINE MADERA EXTERIOR

DESCRIPTION AND NATURE

Decorative nanotechnology-based water protection, for all types of wood. Offers maximum performance, combining features of varnish (waterproof, silky texture) with protection (waterproof, micro-pores). When used outside, always apply to Crea coloured impregnating agent. Maximum colour protection. Easy to apply and maintain. Low presence of odours.

USAGES

Outdoors/Indoors

Suitable for woodwork, doors, windows, moldings, etc.

Recommended previously created with primer

Wood

Apply a maximum of 275 +/- 25 g/m²

PROPERTIES

Waterproof

Does not turn yellow

Good applicability

Does not turn yellow

Water steam transpirable

Odourless when dry

- Endures brusque changes in the weather

- Flexible

- Microporous

- U.V. resistant

TECHNICAL CHARACTERISTICS

Referencia Color CREA LASURE ULTRA SATINADO INCOLORO

Finish Satin

Specific weight 0,98± 0,05 kg/l

Viscosity 18 +/- 2 PO

Solids in volume 29± 1

Solids in weight 32± 1

VOC Cat. e/BA 150/130 (2007/2010):5,91 g/l

Aproximated performance by coat 10-16 m²/L

Dry to touch (20°C HR:60%): 1 - 3 h

Dry to repaint (20°C HR:60%): 12 - 24 H

Colours Colourless.
Cromiservice and Montomix systems (max 5%).

SURFACE PREPAIRING

New surfaces

New woods.

When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment. The base must be free from foreign materials and/or waste matter.

Apply to woods with a moisture content of less than 20%.

Apply to healthy, grease-free, dust-free and dry wood.

Sand down and remove any remnants of glue from the joints and defects from mechanical process.

CREA LASURE ULTRA SATINADO

If the wood shows signs of ageing it must first be sanded down and any dust removed using a plane or other mechanical device.

When CREA LASURE ULTRA SATINADO is applied in exposed conditions, following the directions for restoration and maintenance, the product has been observed to provide wood with optimal resistant protection for up to 10 years. This will always depend on the location / area, conditions and punishment to which the varnished wood is subjected.

Restoring and maintenance

Varnished or painted wood:

- If you have varnished with open-pore wood stains such: remove foreign products, remove any loose or peeling varnish, lightly sand, remove dust from sanding and proceed as on new woods.
- If you have varnished with closed-pore varnishes, sand deeply and if necessary remove by stripping with chemical or mechanical means and proceed as on new woods.
- If you have varnished with cellulosic or polyurethane varnishes, remove by stripping with chemical or mechanical means and proceed as on new woods.
- If you have enamelled with synthetic enamels, remove by stripping by chemical or mechanical means, sand down to wood and proceed as on new woods.
- When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment.
- For items varnished with CREA LASURE ULTRA SATINADO, to maintain their protective efficiency, it is advisable to periodically check the status / appearance of the surfaces. If there is any damage due to impacts and / or scratches, etc., we recommend cleaning and sanding the damaged area and re-varnishing it with with CREA LASURE ULTRA SATINADO

WAY OF USE

Application Notes

Stir the product until perfectly blended.

Apply on clean and dry substrates.

Apply following the recommended dilutions as described in the Application Systems section.

Sand before application to ensure good penetration and smoothing on the wood.

For the first coat, it is recommended that you prime with Fondo Lasure Acqua. Montoxyl Fondo is also suitable.

Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.

Maintain good ventilation conditions while drying.

Do not apply with relative humidity over 80%.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	0-20%
Roller	0-20%
Air-less gun	10-30%
Air-mix gun	10-30%
Aerographic gun	10-30%
Low pressure turbo	10-30%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood indoor/outdoor			
MAX	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	2 x Crea Lasure Ultra Satinado/Mate Color
STD	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Ultra Satinado/Mate Color
Open pore varnished wood			
MAX	Exterior: Anticarcomas Klarxyl Di	Crea Impregnante Color	Crea Lasure Ultra Satinado/Mate Color
STD	Exterior: Anticarcomas Klarxyl Di	Crea Impregnante Color	Crea Lasure Ultra Satinado/Mate Incoloro/Color
Painted or varnished wood (closed pore) outdoor			

Fecha de Alta

27-02-2014

Versión

1C - 20/10/2017

MAX	Exterior: Decapar+ Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Ultra Satinado/Mate Color
STD	Exterior: Decapar+ Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Ultra Satinado/Mate Incoloro/Color

New wood/old outdoor

MAX	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Ultra Satinado/Mate Color
STD	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Ultra Satinado/Mate Incoloro/Color

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.5 L, 2.5 L, 10 L