

CREA PROTECTOR CHALK PAINT



FAMILY
LINE

CREA
MULTISUPERFICIE

DESCRIPTION AND NATURE

Decorative nanotechnology-based water protection, for all types of wood. Offers maximum performance, combining features of varnish (waterproof, silky texture) with protection (waterproof, micro-pores).

Designed to improve finishes created using CREA CHALK PAINT PLUS. Easy application and maintenance. Low odour.

USAGES

Outdoors/Indoors

Recommended previously created with primer

Bases decorated using Crea Chalk Paint

Apply a maximum of 110 +/- 20 g/m² per coat.

PROPERTIES



Waterproof

Does not turn yellow

Good applicability

Does not turn yellow

Water steam transpirable

Odourless when dry

- Endures brusque changes in the weather

- Flexible

- Microporous

- U.V. resistant

TECHNICAL CHARACTERISTICS

Referencia Color	CREA PROTECTOR CHALK PAINT
Finish	Matt
Specific weight	1.020 ± 0.020 Kg/L
Viscosity	20 ± 2 PO
Solids in volume	27 ± 1
Solids in weight	30 ± 1
VOC	Cat. e/BA 150/130 (2007/2010): 5,89 g/l
Aproximated performance by coat	10-16 m ² /L
Dry to touch	(20°C HR: 60%): 1 - 3 h
Dry to repaint	(20°C HR: 60%): 12 - 24 H
Colours	Colourless.

SURFACE PREPAIRING

New surfaces

New woods.

When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment. The base must be free from foreign materials and/or waste matter.

CREA PROTECTOR CHALK PAINT

Apply to woods with a moisture content of less than 20%.

Apply to healthy, grease-free, dust-free and dry wood.

Sand down and remove any remnants of glue from the joints and defects from mechanical process.

If the wood shows signs of ageing it must first be sanded down and any dust removed using a plane or other mechanical device.

- Apply CREA CHALK PAINT PLUS following the instructions on restoration and maintenance. Applying CREA PROTECTOR CHALK PAINT to exterior decorated pieces will improve their resistance.

Restoring and maintenance

Varnished or painted wood:

- If you have varnished with open-pore wood stains such: remove foreign products, remove any loose or peeling varnish, lightly sand, remove dust from sanding and proceed as on new woods.

- If you have varnished with closed-pore varnishes, sand deeply and if necessary remove by stripping with chemical or mechanical means and proceed as on new woods.

- If you have varnished with cellulosic or polyurethane varnishes, remove by stripping with chemical or mechanical means and proceed as on new woods.

- If you have enamelled with synthetic enamels, remove by stripping by chemical or mechanical means, sand down to wood and proceed as on new woods.

- When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment.

- For items varnished with CREA PROTECTOR CHALK PAINT, to maintain their protective efficiency, it is advisable to periodically check the status / appearance of the surfaces. If there is any damage due to impacts and / or scratches, etc., we recommend cleaning and sanding the damaged area and re-varnishing it with with CREA PROTECTOR CHALK PAINT.

WAY OF USE

Application Notes

Stir the product until perfectly blended.

Apply on clean and dry substrates.

Apply following the recommended dilutions as described in the Application Systems section.

Sand before application to ensure good penetration and smoothing on the wood.

Use latex or vinyl gloves.

Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.

Maintain good ventilation conditions while drying.

Do not apply with relative humidity over 80%.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	0-5%
Roller	0-5%
Sponge	0-5%
Flat brush	0-5%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood indoor/outdoor			
MAX	Exterior: Anticarcomas Klearxyl Di	Crea Chalk Paint PLus	2 x Crea Protector Chalk Paint
STD	Crea Chalk Paint PLus	Crea Chalk Paint PLus	Crea Protector Chalk Paint
Open pore varnished wood			
MAX	Exterior: Anticarcomas Klarxyl Di	Crea Chalk Paint PLus	Crea Protector Chalck Paint
STD	Crea Chalk Paint PLus	Crea Chalk Paint PLus	Crea Protector Chalk PAint
Painted or varnished wood (closed pore) outdoor			
MAX	Exterior: Decapar+ Anticarcomas Klearxyl Di	Crea Chalk Paint PLus	2x Crea Protector Chalk Paint

CREA PROTECTOR CHALK PAINT

STD	Exterior: Decapar+ Crea Chalk Paint PLus	Crea Chalk Paint PLus	Crea Protector Chalk Paint
------------	--	-----------------------	----------------------------

New wood/old outdoor

MAX	Exterior: Anticarcomas Klearxyl Di	Crea Chalk Paint PLus	2x Crea Protector Chalck Paint
STD	Crea Chalk Paint PLus	Crea Chalk Paint PLus	Crea Protector Chalck Paint

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.25 L



FAMILY LINE

DESCRIPTION AND NATURE

Decorative nanotechnology-based water protection, for all types of wood. Offers maximum performance, combining features of varnish (waterproof, silky texture) with protection (waterproof, micro-pores).

Designed to improve finishes created using CREA CHALK PAINT PLUS. Easy application and maintenance. Low odour.

USAGES

PROPERTIES




Waterproof

Does not turn yellow

Good applicability

Does not turn yellow

Water steam transpirable



Odourless when dry

- Endures brusque changes in the weather
- Flexible
- Microporous
- U.V. resistant

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1.020 ± 0.020 Kg/L
Viscosity	20 ± 2 PO
Solids in volume	27 ± 1
Solids in weight	30 ± 1
VOC	Cat. e/BA 150/130 (2007/2010): 5,89 g/l
Aproximated performance by coat	10-16 m ² /L
Dry to touch	(20°C HR:60%): 1 - 3 h
Dry to repaint	(20°C HR:60%): 12 - 24 H
Colours	Colourless.

SURFACE PREPARING

New surfaces

New woods.

When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment. The base must be free from foreign materials and/or waste matter.

Apply to woods with a moisture content of less than 20%.

Apply to healthy, grease-free, dust-free and dry wood.

Sand down and remove any remnants of glue from the joints and defects from mechanical process.

If the wood shows signs of ageing it must first be sanded down and any dust removed using a plane or other mechanical device.

- Apply CREA CHALK PAINT PLUS following the instructions on restoration and maintenance. Applying CREA PROTECTOR CHALK PAINT to exterior decorated pieces will improve their resistance.

Restoring and maintenance

Varnished or painted wood:

- If you have varnished with open-pore wood stains such: remove foreign products, remove any loose or peeling varnish, lightly sand, remove dust from sanding and proceed as on new woods.

- If you have varnished with closed-pore varnishes, sand deeply and if necessary remove by stripping with chemical or mechanical means and proceed as on new woods.

- If you have varnished with cellulosic or polyurethane varnishes, remove by stripping with chemical or mechanical means and proceed as on new woods.

- If you have enamelled with synthetic enamels, remove by stripping by chemical or mechanical means, sand down to wood and proceed as on new woods.

- When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment.

- For items varnished with CREA PROTECTOR CHALK PAINT, to maintain their protective efficiency, it is advisable to periodically check the status / appearance of the surfaces. If there is any damage due to impacts and / or scratches, etc., we recommend cleaning and sanding the damaged area and re-varnishing it with CREA PROTECTOR CHALK PAINT.

WAY OF USE

Application Notes

Stir the product until perfectly blended.

Apply on clean and dry substrates.

Apply following the recommended dilutions as described in the Application Systems section.

Sand before application to ensure good penetration and smoothing on the wood.

Use latex or vinyl gloves.

Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.

Maintain good ventilation conditions while drying.

CREA PROTECTOR CHALK PAINT

Fecha de Alta

15-05-2018

Versión

1 - 22/05/2018

Do not apply with relative humidity over 80%.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	0-5%
Roller	0-5%
Sponge	0-5%
Flat brush	0-5%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood indoor/outdoor			
MAX	Exterior: Anticarcomas Klearxyl Di	Crea Chalk Paint PLus	2 x Crea Protector Chalk Paint
STD	Crea Chalk Paint PLus	Crea Chalk Paint PLus	Crea Protector Chalk Paint
Open pore varnished wood			
MAX	Exterior: Anticarcomas Klarxyl Di	Crea Chalk Paint PLus	Crea Protector Chalck Paint
STD	Crea Chalk Paint PLus	Crea Chalk Paint PLus	Crea Protector Chalk PAint
Painted or varnished wood (closed pore) outdoor			
MAX	Exterior: Decapar+ Anticarcomas Klearxyl Di	Crea Chalk Paint PLus	2x Crea Protector Chalk Paint
STD	Exterior: Decapar+ Crea Chalk Paint PLus	Crea Chalk Paint PLus	Crea Protector Chalk Paint
New wood/old outdoor			
MAX	Exterior: Anticarcomas Klearxyl Di	Crea Chalk Paint PLus	2x Crea Protector Chalck Paint
STD	Crea Chalk Paint PLus	Crea Chalk Paint PLus	Crea Protector Chalck Paint

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

0.25 L