

Fecha de Alta

26-02-2014

Versión

1C - 08/06/2020



FAMILY LINE

CREA
FONDO

DESCRIPTION AND NATURE

Protective water base for all types of wood. Penetrates and highlights veins. The combination of Crea Impregnante Coloreado and an exterior finish offers maximum protection against solar radiation and durability of the wood. To repaint with lasures to the water. Improves adhesion, evens absorptions and improves the appearance of the finish, increasing its performance. Low odor. Indoor / outdoor use.

USAGES

Outdoors/Indoors

Exotic woods and rich in tannins in general.

Recommended in high mountain and coastal areas for porous finishes, repaintable with water-based woodstain.

Wood staining

PROPERTIES

- Penetration power
- Do not turn film on the surface, for which do not change its appearance
- For maximum protection outdoors, give it coloured
- Water resistant
- Ready for use. Do not dilute
- Good adhesion
- Re-paintable with water based lassures
- Easily applicable
- No cracking at all
- Microporous
- U.V. resistant
- Excellent protection against weather factors
- Water repellent

TECHNICAL CHARACTERISTICS

Referencia Color	CREA IMPREGNANTE INCOLORO
Finish	Matt
Specific weight	0,99± 0,05 kg/l
Viscosity	12 +/- 1 SG
Solids in volume	7± 1
Solids in weight	7± 1
VOC	Cat. e/BA 150/130 (2007/2010): 4,64 g/l
Aproximated performance by coat	10-15 m²/L
Dry to touch	(20°C HR: 60%): Aprox. 30 min.
Dry to repaint	(20°C HR: 60%): 6-12 h
Colours	Pine, Oak, Walnut, Rosewood, Chestnut, Teak, Mahogany. They can be mixed to get new colors. The Colorless, recommended to reduce the intensity of the desired tone.

SURFACE PREPAIRING

New surfaces

New woods:

- Outdoors, protect the wood with Klearxyl Di Anticarcomas from attack by fungi and xylophagous insects.

Fecha de Alta

26-02-2014

Versión

1C - 08/06/2020

- Apply on wood with a moisture content of less than 20%.
- Apply on healthy, well-degreased, dust-free and dry woods.
- Sand and eliminate possible glue residues in the assemblies and machining failures.
- If the wood shows signs of aging, it must be previously sanded and dust removed by brushing or any other mechanical means.

Restoring and maintenance

Varnished or painted woods:

- Outdoors, protect the wood with Klearxyl Di Anticarcomas from attack by fungi and xylophagous insects.
- If they have been varnished with lasur, sand lightly and remove dust. Proceed like new wood.
- If they have been varnished, remove badly adhered or poorly maintained areas by pickling or mechanical means, remove the dust resulting from sanding and proceed as on new woods.
- If they have been varnished with cellulose or polyurethane varnishes, remove by pickling or by mechanical means, remove sanded dust and proceed as on new woods.
- If they have been enameled with synthetic enamel, remove by pickling or by mechanical means, remove dust and proceed as on new woods.

WAY OF USE

Application notes

- Apply on clean and dry substrates.
- Apply following the dilutions recommended in the Application Systems section.
- Pre-sand to guarantee a good penetration and leveling on the wood.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- Maintain good ventilation conditions during the drying time.
- Do not apply with relative humidity higher than 80%.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	Al uso
Roller	Al uso
Air-less gun	Al uso
Air-mix gun	Al uso
Aerographic gun	Al uso
Dipping	Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Painted or varnished wood (closed pore) indoor			
MAX	Decapar+ Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Color
STD	Decapar+ Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Incoloro/Color
Open pore varnished wood			
MAX	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Color
STD	Exteriro: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Incoloro/Color
Indoor wood			
MAX	Crea Impregnante Incoloro/Color		Crea Lasure y gama Crea Acabados
STD	Crea Impregnante Incoloro/Color		Crea Lasure y gama Crea Acabados
Garden furniture, wooden and similar			
MAX	Exterior : Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Color

Fecha de Alta

26-02-2014

Versión

1C - 08/06/2020

STD Exterior : Anticarcomas Klearxyl Di Crea Impregnante Color Crea Lasure y gama Crea Acabados Incoloro/Color

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.5 L, 2.5 L, 10 L



FAMILY LINE

DESCRIPTION AND NATURE

Protective water base for all types of wood. Penetrates and highlights veins. The combination of Crea Impregnante Coloreado and an exterior finish offers maximum protection against solar radiation and durability of the wood. To repaint with lasures to the water. Improves adhesion, evens absorptions and improves the appearance of the finish, increasing its performance. Low odor. Indoor / outdoor use.

USAGES

PROPERTIES

- Penetration power
- Do not turn film on the surface, for which do not change its appearance
- For maximum protection outdoors, give it coloured
- Water resistant
- Ready for use. Do not dilute
- Good adhesion
- Re-paintable with water based lasures
- Easily applicable
- No cracking at all
- Microporous
- U.V. resistant
- Excellent protection against weather factors
- Water repellent

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	0,99± 0,05 kg/l
Viscosity	12 +/- 1 SG
Solids in volume	7± 1
Solids in weight	7± 1
VOC	Cat. e/BA 150/130 (2007/2010):4,64 g/l
Aproximated performance by coat	10-15 m²/L

Dry to touch	(20°C HR: 60%):Aprox. 30 min.
Dry to repaint	(20°C HR: 60%):6-12 h
Colours	Pine, Oak, Walnut, Rosewood, Chestnut, Teak, Mahogany. They can be mixed to get new colors. The Colorless, recommended to reduce the intensity of the desired tone.

SURFACE PREPAIRING

New surfaces

New woods:

- Outdoors, protect the wood with Klearxyl Di Anticarcomas from attack by fungi and xylophagous insects.
- Apply on wood with a moisture content of less than 20%.
- Apply on healthy, well-degreased, dust-free and dry woods.
- Sand and eliminate possible glue residues in the assemblies and machining failures.
- If the wood shows signs of aging, it must be previously sanded and dust removed by brushing or any other mechanical means.

Restoring and maintenance

Varnished or painted woods:

- Outdoors, protect the wood with Klearxyl Di Anticarcomas from attack by fungi and xylophagous insects.
- If they have been varnished with lasur, sand lightly and remove dust. Proceed like new wood.
- If they have been varnished, remove badly adhered or poorly maintained areas by pickling or mechanical means, remove the dust resulting from sanding and proceed as on new woods.
- If they have been varnished with cellulose or polyurethane varnishes, remove by pickling or by mechanical means, remove sanded dust and proceed as on new woods.
- If they have been enameled with synthetic enamel, remove by pickling or by mechanical means, remove dust and proceed as on new woods.

WAY OF USE

Application notes

- Apply on clean and dry substrates.
- Apply following the dilutions recommended in the Application Systems section.
- Pre-sand to guarantee a good penetration and leveling on the wood.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- Maintain good ventilation conditions during the drying time.
- Do not apply with relative humidity higher than 80%.

Solvent for dilution and cleaning

Water

Way of use

Aproximate dilution

Painting brush	Al uso
Roller	Al uso
Air-less gun	Al uso
Air-mix gun	Al uso
Aerographic gun	Al uso

Fecha de Alta

26-02-2014

Versión

1C - 08/06/2020

Dipping

Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Painted or varnished wood (closed pore) indoor			
MAX	Decapar+ Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Color
STD	Decapar+ Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Incoloro/Color
Open pore varnished wood			
MAX	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Color
STD	Exteriro: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Incoloro/Color
Indoor wood			
MAX	Crea Impregnante Incoloro/Color		Crea Lasure y gama Crea Acabados Color
STD	Crea Impregnante Incoloro/Color		Crea Lasure y gama Crea Acabados Incoloro/Color
Garden furniture, wooden and similar			
MAX	Exterior : Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Color
STD	Exterior : Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure y gama Crea Acabados Incoloro/Color

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

0.5 L, 2.5 L, 10 L