

Fecha de Alta

26-02-2014

Versión

12 - 20/10/2017



FAMILY

CREA

LINE

MADERA EXTERIOR

DESCRIPTION AND NATURE

"Woodstain"-type water protector, developed with nano-particle technology, for protection of interior / exterior wood, reinforced with U.V. protection agents. Maximum colour protection.

USAGES

Outdoors/Indoors

For maximum protection, finish in colour.

Apply a maximum of 275 +/- 25 g/m²

Recommended in high mountain and coastal areas for porous finishes, repaintable with water-based woodstain.

PROPERTIES

Penetration power

Provides open pore finish

Does not turn yellow

Penetration power

- Do not apply white media, you can amarillarlos slightly, but does not alter the properties of the product.

no need of sanding, but easy to do once dried

recommended number of coats : 2-3 coats over new wood, 1-2 coats as maintenance

Does not turn yellow

No cracking at all

Does not form blisters

Water steam transpirable

Odourless when dry

- Endures brusque changes in the weather

- Flexible

- Microporous

- Highlights the wood's natural grain

- U.V. resistant

- May be used as a base when diluted, thus nourishing the wood

TECHNICAL CHARACTERISTICS

Referencia Color	CREA LASURE SATINADO INCOLORO
Finish	Satin
Specific weight	0,98± 0,05 kg/l
Viscosity	18 +/- 2 PO
Solids in volume	20± 1
Solids in weight	23± 1
VOC	Cat. e/BA 150/130 (2007/2010):5,92 g/l
Aproximated performance by coat	10-16 m ² /L

Dry to touch (20°C HR:60%): 2-4 h. Total: 12-24 h

Dry to repaint (20°C HR:60%): 12-24 h

Colours Colors: Pino, Roble, Nogal, Palisandro, Castaño, Teca, Caoba.
Colourless, reduces tone intensity.

SURFACE PREPAIRING

Fecha de Alta

26-02-2014

Versión

12 - 20/10/2017

New surfaces

New woods.

When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment. The base must be free from foreign materials and/or waste matter.

Apply to woods with a moisture content of less than 20%.

Apply to healthy, grease-free, dust-free and dry wood.

Sand down and remove any remnants of glue from the joints and defects from mechanical process.

If the wood shows signs of ageing it must first be sanded down and any dust removed using a plane or other mechanical device.

When CREA LASURE SATINADO is applied in exposed conditions, following the directions for restoration and maintenance, the product has been observed to provide wood with optimal resistant protection for up to 7 years. This will always depend on the location / area, conditions and punishment to which the varnished wood is subjected.

Restoring and maintenance

Varnished or painted wood:

- If you have varnished with open-pore wood stains such: remove foreign products, remove any loose or peeling varnish, lightly sand, remove dust from sanding and proceed as on new woods.

- If you have varnished with closed-pore varnishes, sand deeply and if necessary remove by stripping with chemical or mechanical means and proceed as on new woods.

- If you have varnished with cellulosic or polyurethane varnishes, remove by stripping with chemical or mechanical means and proceed as on new woods.

- If you have enamelled with synthetic enamels, remove by stripping by chemical or mechanical means, sand down to wood and proceed as on new woods.

- When working outside, protect wood from attacks by fungi and xylophagous insects with Klearxyl Di Wood-Borer Treatment.

- For items varnished with CREA LASURE SATINADO, to maintain their protective efficiency, it is advisable to periodically check the status / appearance of the surfaces. If there is any damage due to impacts and / or scratches, etc., we recommend cleaning and sanding the damaged area and re-varnishing it with CREA LASURE SATINADO

WAY OF USE

Application Notes

Stir the product until perfectly blended.

Apply on clean and dry substrates.

Apply following the recommended dilutions as described in the Application Systems section.

Sand before application to ensure good penetration and smoothing on the wood.

For the first coat, it is recommended that you prime with Crea Impregnante.

Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.

Maintain good ventilation conditions while drying.

Do not apply with relative humidity over 80%.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	fondo: 10-30%
Roller	10-30%
Air-less gun	30-50%
Air-mix gun	30-50%
Aerographic gun	10-30%
Low pressure turbo	10-30%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Open pore varnished wood			
MAX	Exterior: Decapar+ Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Satinado Color
STD	Exterior: Decapar+ Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Satinado Incoloro/Color

Fecha de Alta

26-02-2014

Versión

12 - 20/10/2017

New /old wood indoor/outdoor

MAX	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Satinado Color
STD	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Satinado Incolor/Color

Painted or varnished wood (closed pore) outdoor

MAX	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Satinado Color
STD	Exterior: Anticarcomas Klearxyl Di	Crea Impregnante Color	Crea Lasure Satinado Incoloro/Color

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.5 L, 2.5 L