



FAMILY CREA / SISTEMAS TINTOMÉTRICOS

LINE MADERA INTERIOR

DESCRIPTION AND NATURE

Water-based varnish, made with latest technology acrylic emulsions, for varnishing, protecting and decorating all types of interior wood.

USAGES

Indoors
Exterior with protection.
Ideal for general carpentry.
Wood
Suitable for furniture and doors
Cement
Plaster
Cement
Concrete
Brick
Apply a maximum of 275 +/- 25 g/m²
Use over clean woods

PROPERTIES

- Good adhesion
- Good resistance
- Does not turn yellow
- Flexible
- Microporous
- Highlights the wood's natural grain
- Excellent covering
- Odourless
- Superior waterproofing

TECHNICAL CHARACTERISTICS

Referencia Color	CREA BARNIZ INTERIOR MATE INCOLORO
Finish	Matt
Specific weight	1 ± 0,05 kg/l
Viscosity	13 +/- 2 PO
Solids in volume	23 ± 1
Solids in weight	27 ± 1
VOC	Cat. e/BA 150/130 (2007/2010): 4,80 g/l
Aproximated performance by coat	10-15 m ² /L
Dry to touch	(20°C HR: 60%): 1 - 3 h
Dry to repaint	(20°C HR: 60%): 16 - 24 h
Colours	Colorless, Oak, Walnut, Chestnut, Teak, Mahogany.

SURFACE PREPAIRING

New surfaces

New wood:

- The support must be free of any remaining product or residue.

CREA BARNIZ INTERIOR MATE

- Apply in which the moisture content is less than 20%.
- Apply on healthy, well degreased, dust-free and dry wood.
- Sand and remove any remaining bonding glue.
- If the wood shows signs of aging, sand in advance, then remove the dust with a brush.

Restoring and maintenance

Varnished or painted wood:

- If the wood has been varnished with open pore stains: remove the remains of old products, remove badly adhered or in poor condition, sand lightly, remove dust after sanding and then proceed as in new wood.
- If the wood has been varnished with closed-pore varnishes or another similar product, sand well and, if necessary, remove the product by stripping or using mechanical means, then proceed as in new wood.
- If the wood has been varnished with cellulose or polyurethane varnishes, remove them by stripping or mechanical means, then proceed as in new wood.
- If the wood has been lacquered with synthetic lacquers, remove them by pickling or using mechanical means, sand to the wood, then proceed as in new wood.

WAY OF USE

Application notes

- Stir the product until it is perfectly homogenized.
- Apply on clean and dry substrates.
- Apply following the dilutions recommended in the Application Systems section.
- Pre-sand to guarantee a good penetration and leveling on the wood.
- In the first hand, it is advisable to prime preferably with Crea Impregnante.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- Maintain good ventilation conditions during the drying time.
- Do not apply with relative humidity higher than 80%

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Air-mix gun	0-10%
Aerographic gun	5-10%
Brush, Roller	0-20%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Indoor wood (closed pore)			
MAX	Crea Impregnante	Crea Barniz Interior Brillo/Satinado/Mate	Crea Barniz Interior Brillo/Satinado/Mate
STD	Crea Barniz Interior Brillo/Satinado/Mate		Crea Barniz Interior Brillo/Satinado/Mate

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.5 L, 2.5 L



FAMILY LINE

DESCRIPTION AND NATURE

Water-based varnish, made with latest technology acrylic emulsions, for varnishing, protecting and decorating all types of interior wood.

USAGES

PROPERTIES

- Good adhesion
- Good resistance
- Does not turn yellow
- Flexible
- Microporous
- Highlights the wood's natural grain
- Excellent covering
- Odourless
- Superior waterproofing

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1 ± 0,05 kg/l
Viscosity	13 +/- 2 PO
Solids in volume	23 ± 1
Solids in weight	27 ± 1


VOC Cat. e/BA 150/130 (2007/2010): 4,80 g/l

Aproximated performance by coat 10-15 m²/L

Dry to touch	(20°C HR:60%): 1 - 3 h
Dry to repaint	(20°C HR:60%): 16 - 24 h
Colours	Colorless, Oak, Walnut, Chestnut, Teak, Mahogany.

SURFACE PREPAIRING

CREA BARNIZ INTERIOR MATE



New surfaces

New wood:

- The support must be free of any remaining product or residue.
- Apply in which the moisture content is less than 20%.
- Apply on healthy, well degreased, dust-free and dry wood.
- Sand and remove any remaining bonding glue.
- If the wood shows signs of aging, sand in advance, then remove the dust with a brush.

Restoring and maintenance

Varnished or painted wood:

- If the wood has been varnished with open pore stains: remove the remains of old products, remove badly adhered or in poor condition, sand lightly, remove dust after sanding and then proceed as in new wood.
- If the wood has been varnished with closed-pore varnishes or another similar product, sand well and, if necessary, remove the product by stripping or using mechanical means, then proceed as in new wood.
- If the wood has been varnished with cellulose or polyurethane varnishes, remove them by stripping or mechanical means, then proceed as in new wood.
- If the wood has been lacquered with synthetic lacquers, remove them by pickling or using mechanical means, sand to the wood, then proceed as in new wood.

WAY OF USE

Application notes

- Stir the product until it is perfectly homogenized.
- Apply on clean and dry substrates.
- Apply following the dilutions recommended in the Application Systems section.
- Pre-sand to guarantee a good penetration and leveling on the wood.
- In the first hand, it is advisable to prime preferably with Crea Impregnante.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- Maintain good ventilation conditions during the drying time.
- Do not apply with relative humidity higher than 80%

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Air-mix gun	0-10%
Aerographic gun	5-10%
Brush, Roller	0-20%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Indoor wood (closed pore)			
MAX	Crea Impregnante	Crea Barniz Interior Brillo/Satinado/Mate	Crea Barniz Interior Brillo/Satinado/Mate
STD	Crea Barniz Interior Brillo/Satinado/Mate		Crea Barniz Interior Brillo/Satinado/Mate

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

771437

Fecha de Alta

27-02-2014

Versión

7 - 08/06/2020

CREA BARNIZ INTERIOR MATE



Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

0.5 L, 2.5 L