

CREA ACEITE PROTECTOR 2 EN 1



FAMILY

CREA

LINE

MADERA JARDIN

DESCRIPTION AND NATURE

Protector for garden furniture and platforms. Formulated with the latest generation nanotechnological additives and water resins, combined with oils that penetrate and nourish the wood, maintaining its natural appearance. Weather resistant, with UV filters. Easy application and maintenance. Low odor. Water saturated wood saturator.

USAGES

Outdoors/Indoors

Wood

Use over clean woods

Penetrates, protects and nourishes wood

Weather resistant, with UV filters

Breathable and water repellent

Garden furniture, decks.

PROPERTIES

- Penetration power
- For maximum protection outdoors, give it coloured
- Water resistant
- Ready for use. Do not dilute
- Good adhesion
- Do not turn film on the surface
- Easily applicable
- No cracking at all
- Microporous
- U.V. resistant
- Excellent protection against weather factors

TECHNICAL CHARACTERISTICS

Referencia Color	CREA ACEITE PROTECTOR 2 EN 1 INCOLORO
Finish	Matt
Specific weight	0,99± 0,05 kg/l
Viscosity	13 +/- 2 SG
Solids in volume	13± 1
Solids in weight	14± 1
VOC	Cat. e/BA 150/130 (2007/2010):4,64 g/l
Aproximated performance by coat	10-14 m ² /L

Dry to touch	(20°C HR: 60%): 30 - 60 min
Dry to repaint	(20°C HR: 60%): 6-12 h
Colours	Colorless, Yellow Pine, Teak, Reed Green, Walnut, Ipe.

SURFACE PREPAIRING

New surfaces

New woods:

- The support must be free of foreign products and / or residues.
- Apply on wood with a moisture content of less than 20%.

Fecha de Alta

27-02-2014

Versión

9 - 23/07/2020

- Apply on healthy, well-degreased, dust-free and dry woods.
- Sand and eliminate possible glue residues in the assemblies and machining failures.
- If the wood shows signs of aging, it must be previously sanded and dust removed by brushing or any other mechanical means.

Restoring and maintenance

Varnished or painted woods:

- If they have been varnished with lasures or the like, remove badly adhered areas or in poor condition, it is recommended to sand lightly, remove the dust resulting from sanding and proceed as on new woods.
- If they have been varnished with cellulose or polyurethane varnishes, remove them by pickling or by mechanical means and proceed as on new woods.
- If they have been enameled with synthetic enamel, remove by stripping or by mechanical means and proceed as on new woods.
- If they have been treated with nutrients or with Protective Oil, apply directly.

WAY OF USE

Application notes

- Stir the product until it is perfectly homogenized.
- Apply on clean and dry substrates.
- Apply following the dilutions recommended in the Application Systems section.
- Pre-sand to guarantee a good penetration and leveling on the wood.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- Maintain good ventilation conditions during the drying time.
- Do not apply with relative humidity higher than 80%.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	Al uso
Roller	Al uso
Air-less gun	Al Uso
Air-mix gun	Al uso
Aerographic gun	Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood indoor/outdoor			
MAX	Klearxyl Di Anticarcomas	Crea Aceite Protector 2 en 1	Crea Aceite Protector 2 en 1
STD	Crea Aceite Protector 2 en 1		Crea Aceite Protector 2 en 1
varnished or painted wood outdoor/indoor			
MAX	Decapar+ Klearxyl Di Anticarcomas	Crea Aceite Protector 2 en 1	Crea Aceite Protector 2 en 1
STD	Decapar+ Crea Aceite Protector 2 en 1		Crea Aceite Protector 2 en 1
Garden furniture, wooden and similar			
MAX	Klearxyl Di Anticarcomas	Crea Aceite Protector 2 en 1	Crea Aceite Protector 2 en 1
STD	Crea Aceite Protector 2 en 1		Crea Aceite Protector 2 en 1

SECURITY

Fecha de Alta

27-02-2014

Versión

9 - 23/07/2020

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adecuate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.5 L, 2.5 L



**FAMILY
LINE**

DESCRIPTION AND NATURE

Protector for garden furniture and platforms. Formulated with the latest generation nanotechnological additives and water resins, combined with oils that penetrate and nourish the wood, maintaining its natural appearance. Weather resistant, with UV filters. Easy application and maintenance. Low odor. Water saturated wood saturator.

USAGES

PROPERTIES

- Penetration power
- For maximum protection outdoors, give it coloured
- Water resistant
- Ready for use. Do not dilute
- Good adhesion
- Do not turn film on the surface
- Easely applicable
- No cracking at all
- Microporous
- U.V. resistant
- Excellent protection against weather factors

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	0,99± 0,05 kg/l
Viscosity	13 +/- 2 SG
Solids in volume	13± 1

Fecha de Alta

27-02-2014

Versión

9 - 23/07/2020

Solids in weight	14± 1
VOC	Cat. e/BA 150/130 (2007/2010): 4,64 g/l
Aproximated performance by coat	10-14 m ² /L

Dry to touch	(20°C HR: 60%): 30 - 60 min
Dry to repaint	(20°C HR: 60%): 6-12 h
Colours	Colorless, Yellow Pine, Teak, Reed Green, Walnut, Ipe.

SURFACE PREPAIRING

New surfaces

New woods:

- The support must be free of foreign products and / or residues.
- Apply on wood with a moisture content of less than 20%.
- Apply on healthy, well-degreased, dust-free and dry woods.
- Sand and eliminate possible glue residues in the assemblies and machining failures.
- If the wood shows signs of aging, it must be previously sanded and dust removed by brushing or any other mechanical means.

Restoring and maintenance

Varnished or painted woods:

- If they have been varnished with lasures or the like, remove badly adhered areas or in poor condition, it is recommended to sand lightly, remove the dust resulting from sanding and proceed as on new woods.
- If they have been varnished with cellulose or polyurethane varnishes, remove them by pickling or by mechanical means and proceed as on new woods.
- If they have been enameled with synthetic enamel, remove by stripping or by mechanical means and proceed as on new woods.
- If they have been treated with nutrients or with Protective Oil, apply directly.

WAY OF USE

Application notes

- Stir the product until it is perfectly homogenized.
- Apply on clean and dry substrates.
- Apply following the dilutions recommended in the Application Systems section.
- Pre-sand to guarantee a good penetration and leveling on the wood.
- Do not apply the product at high temperatures, or on surfaces exposed to strong insolation.
- Maintain good ventilation conditions during the drying time.
- Do not apply with relative humidity higher than 80%.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	Al uso
Roller	Al uso
Air-less gun	Al Uso
Air-mix gun	Al uso
Aerographic gun	Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood indoor/outdoor			
MAX	Klearxyl Di Anticarcomas	Crea Aceite Protector 2 en 1	Crea Aceite Protector 2 en 1
STD	Crea Aceite Protector 2 en 1		Crea Aceite Protector 2 en 1


CREA ACEITE PROTECTOR 2 EN 1

Fecha de Alta

27-02-2014

Versión

9 - 23/07/2020



varnished or painted wood outdoor/indoor

MAX	Decapar+ Klearxyl Di Anticarcomas	Crea Aceite Protector 2 en 1	Crea Aceite Protector 2 en 1
STD	Decapar+ Crea Aceite Protector 2 en 1		Crea Aceite Protector 2 en 1

Garden furniture, wooden and similar

MAX	Klearxyl Di Anticarcomas	Crea Aceite Protector 2 en 1	Crea Aceite Protector 2 en 1
STD	Crea Aceite Protector 2 en 1		Crea Aceite Protector 2 en 1

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

0.5 L, 2.5 L