

CREA TARIMAS ANTIDESLIZANTE



FAMILY TRATAMIENTOS DE LA MADERA

LINE CREA JARDIN

DESCRIPTION AND NATURE

-Protector for exterior/interior decking and floors where an anti-slip effect is required. Resistant to water, UV and the elements. Easy application and maintenance. Low odour.

High quality non-slip particles that ensure a finish that is pleasant on the foot.

Classification of floors according to Slipperiness.

UNE-ENV 12633:2003 Appendix A Pendulum

SR > 45 Class 3

Classification according to average slope angle.

DIN 51097:1992

Barefoot test

> 24° Group C

Results obtained with the painting system described below.

USAGES

Outdoors/Indoors

Maintenance paint

Water repellent

Wood

Suitable for parquet and wooden floors

Decking and wood floors around swimming pools

Suitable for parquet and wood floors

Non-slip effect

Use over clean woods

PROPERTIES

- Penetration power
- Water resistant
- Good adhesion
- Environmentally friendly.
- Do not apply white media, you can amarillarlos slightly, but does not alter the properties of the product.
- Outdoor resistance
- Easely applicable
- High performance
- Reinforced with U.V. filter
- Non-slip effect
- Resistance to abrasion and wear
- Apply a maximum of 120 g/m2 in each hand. Evenly distribute the anti-slip particles

TECHNICAL CHARACTERISTICS

Referencia Color CREA TARIMAS ANTIDESLIZANTE INCOLORO

Finish Matt

Specific weight 1,03± 0,05 kg/l

Viscosity 60 +/- 5 SG

Solids in volume 23± 1

Solids in weight 28± 1

VOC Cat. e/BA 150/130 (2007/2010):62,52 g/l

Aproximated performance by coat 8-12 m²/L

Dry to touch Aprox. 60 min.

Dry to repaint Aprox. 16 - 24 h

Colours

Colorless

SURFACE PREPARING

New surfaces

New wood:

- The base must be free from foreign products and/or residue.
- Apply to woods with a moisture content lower than 20%.
- Apply to healthy, grease-free, dust-free, dry wood.
- Sand down to remove any traces of glue in joints and milling defects.
- If the wood shows signs of aging must be previously sanded and removed by brushing or any other mechanical means.
- Apply a maximum of 120 g/m² with each coat. Distribute the non-slip particles evenly.

Restoring and maintenance

Varnished or painted wood:

- If the wood has been varnished with open pore and the condition of the wood allows, remove varnish that is loose or in poor condition, gently sand, remove the sanding dust and proceed as with new wood.
- If it has been varnished with cellulose or polyurethane varnishes and the condition of the wood allows, remove by stripping with chemical or mechanical means and proceed as with new wood.
- If they have been enamelled with synthetic enamel remove by pickling or by mechanical means and proceed as on new woods.
- Apply a maximum of 120 g/m² with each coat. Distribute the non-slip particles evenly.

Maintenance:

- Cleaning with low-pressure water cleaner, taking care to ensure that the water temperature is not high.
- Avoid cleaning during the middle of the day, and check that the base is not hot; major temperature differences accelerate degradation of the varnish.
- When there is a noticeable loss of non-slip properties, perform maintenance. If there is little loss of the original colour, only the finishing coat/s is/are necessary.

WAY OF USE

Application notes

- Stir the product until perfectly blended.
- Manually from bottom to top, or slowly using mechanical means.
- Apply on clean and dry substrates.
- Ensure that the wood does not have traces of oil or other foreign substances.
- Sand before application to ensure good penetration and smooth finish on the wood. Sand first with 40-80 grain; if the result is too uneven, smooth with 150-220 sandpaper.
- Dry wood with a moisture content lower than 20%.
- The first coat should be with Crea impregnante color to ensure optimum slip resistance.
- Dry wood with a moisture content lower than 20%.
- Sand gently if the wood has risen in areas.
- Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.
- Ensure the area is well ventilated while the product is drying.
- Do not apply with relative humidity over 80%
- Apply a maximum of 120 g/m² with each coat. Distribute the non-slip particles evenly.
- Test the characteristics according to the base used to ensure the best slip resistance results.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	Al uso
Roller	Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood indoor/outdoor			
MAX	Crea Impregnante con Color	Crea Tarimas Antideslizante	Crea Tarimas Antideslizante

CREA TARIMAS ANTIDESLIZANTE

STD Crea Impregante con Color Crea Tarimas Antideslizante

varnished or painted wood outdoor/indoor

MAX Decapar+Crea Impregnante Color Crea Tarimas Antideslizante Crea Tarimas Antideslizante

STD Decapar+Crea Impregnante Color Crea Tarimas Antideslizante

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances.As it is impossible to stablish an adecuate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

0.5 L, 2.5 L



FAMILY LINE

DESCRIPTION AND NATURE


-Protector for exterior/interior decking and floors where an anti-slip effect is required. Resistant to water, UV and the elements. Easy application and maintenance. Low odour.
High quality non-slip particles that ensure a finish that is pleasant on the foot.
Classification of floors according to Slipperiness.
UNE-ENV 12633:2003 Appendix A Pendulum
SR > 45 Class 3
Classification according to average slope angle.
DIN 51097:1992
Barefoot test
> 24° Group C
Results obtained with the painting system described below.

USAGES

PROPERTIES

- Penetration power
- Water resistant
- Good adhesion
- Environmentally friendly.

CREA TARIMAS ANTIDESLIZANTE



- Do not apply white media, you can amarillarlos slightly, but does not alter the properties of the product.
- Outdoor resistance
- Easely applicable
- High performance
- Reinforced with U.V. filter
- Non-slip effect
- Resistance to abrasion and wear
- Apply a maximum of 120 g/m2 in each hand. Evenly distribute the anti-slip particles

TECHNICAL CHARACTERISTICS

Referencia Color

Finish	Matt
Specific weight	1,03± 0,05 kg/l
Viscosity	60 +/- 5 SG
Solids in volume	23± 1
Solids in weight	28± 1
VOC	Cat. e/BA 150/130 (2007/2010):62,52 g/l
Aproximated performance by coat	8-12 m ² /L
Dry to touch	Aprox. 60 min.
Dry to repaint	Aprox. 16 - 24 h
Colours	Colorless

SURFACE PREPARING

New surfaces

New wood:

- The base must be free from foreign products and/or residue.
- Apply to woods with a moisture content lower than 20%.
- Apply to healthy, grease-free, dust-free, dry wood.
- Sand down to remove any traces of glue in joints and milling defects.
- If the wood shows signs of aging must be previously sanded and removed by brushing or any other mechanical means.
- Apply a maximum of 120 g/m2 with each coat. Distribute the non-slip particles evenly.

Restoring and maintenance

Varnished or painted wood:

- If the wood has been varnished with open pore and the condition of the wood allows, remove varnish that is loose or in poor condition, gently sand, remove the sanding dust and proceed as with new wood.
- If it has been varnished with cellulose or polyurethane varnishes and the condition of the wood allows, remove by stripping with chemical or mechanical means and proceed as with new wood.
- If they have been enamelled with synthetic enamel remove by pickling or by mechanical means and proceed as on new woods.
- Apply a maximum of 120 g/m2 with each coat. Distribute the non-slip particles evenly.

Maintenance:


- Cleaning with low-pressure water cleaner, taking care to ensure that the water temperature is not high.
- Avoid cleaning during the middle of the day, and check that the base is not hot; major temperature differences accelerate degradation of the varnish.
- When there is a noticeable loss of non-slip properties, perform maintenance. If there is little loss of the original colour, only the finishing coat/s is/are necessary.

WAY OF USE

Application notes

- Stir the product until perfectly blended.
- Manually from bottom to top, or slowly using mechanical means.
- Apply on clean and dry substrates.
- Ensure that the wood does not have traces of oil or other foreign substances.
- Sand before application to ensure good penetration and smooth finish on the wood. Sand first with 40-80 grain; if the result

CREA TARIMAS ANTI DESLIZANTE



is too uneven, smooth with 150-220 sandpaper.

- Dry wood with a moisture content lower than 20%.
- The first coat should be with Crea impregnante color to ensure optimum slip resistance.
- Dry wood with a moisture content lower than 20%.
- Sand gently if the wood has risen in areas.
- Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.
- Ensure the area is well ventilated while the product is drying.
- Do not apply with relative humidity over 80%
- Apply a maximum of 120 g/m2 with each coat. Distribute the non-slip particles evenly.
- Test the characteristics according to the base used to ensure the best slip resistance results.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	Al uso
Roller	Al uso

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
New wood indoor/outdoor			
MAX	Crea Impregnante con Color	Crea Tarimas Antideslizante	Crea Tarimas Antideslizante
STD	Crea Impregnante con Color		Crea Tarimas Antideslizante
varnished or painted wood outdoor/indoor			
MAX	Decapar+Crea Impregnante Color	Crea Tarimas Antideslizante	Crea Tarimas Antideslizante
STD	Decapar+Crea Impregnante Color		Crea Tarimas Antideslizante

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

PACKINGS

0.5 L, 2.5 L