

CREA ESMALTE LACA SATINADO



FAMILY

CREA

LINE

MULTISUPERFICIE

DESCRIPTION AND NATURE

Satin finish multi-adhesive made with acrylic copolymers and polyurethane compounds. Good block resistance. Ready to use. Odourless.

USAGES

Outdoors/Indoors

Plaster

Plaster

Stone

Metal after priming

Construction

Cement mortars

Wood

PROPERTIES

Levelling

Penetration power

Strong resistance to the atmospherical factors

Water resistant

Excellent gloss maintenance

Penetration power

Strong resistance to the atmospherical factors

- Good coverage capacity

Good applicability

- Good coverage capacity

Water steam transpirable

Odourless when dry

Formulated with non toxic pigment and composites

TECHNICAL CHARACTERISTICS

Referencia Color	CREA ESMALTE LACA SATINADO BLANCO
Finish	Satin
Specific weight	1,26± 0,05 kg/l
Viscosity	20 +/- 3 PO
Solids in volume	40± 1
Solids in weight	53± 1
VOC	Cat. d/BA 150/130 (2007/2010): 130,00 g/l
Aproximated performance by coat	12-14 m ² /L

Dry to touch (20°C HR: 60%): 1 h

Dry to repaint (20°C HR: 60%): 5-6 h

Colours White and colours chart CREA.

SURFACE PREPAIRING

French norm DTU 59.1

CREA ESMALTE LACA SATINADO

New surfaces

Plaster, cement and derivatives:

1. Wait until fully hardened.
2. Clean possible efflorescence from the base and neutralise alkaline surfaces. Use a suitable filler to eliminate defects in the base.
3. Apply a fixative or diluted Crea Esmalte Laca.

New woods:

1. Apply on wood with less than 20% moisture content. Healthy, dry wood, well cleaned of dust and grease.
2. If the wood shows signs of ageing, it should first be sanded and primed, and dust removed by brushing or any other mechanical means.
3. Before applying the paint, prime with Crea Selladora .

Iron and derivatives:

1. Apply to dry bases, well cleaned of dust and grease. If they show signs of oxidation, rust must be removed through brushing or any other mechanical means.
2. Next, before application, prime with Crea Imprimación Antioxidante .

Galvanised and light metals:

1. Remove all grease and check the adhesion.
2. If priming is necessary, we recommend Crea Imprimación Multiadherente .

Restoring and maintenance

Plaster, cement and painted derivatives:

1. Remove products from the base which are flaking or in poor condition, and raise a tooth on smooth surfaces by sanding or other mechanical means. Check the adhesion and treat as new.

Varnished or painted woods:

1. If they are varnished or painted with an open-pored glaze, remove foreign products, remove any loose or peeling products, sand lightly, remove dust from sanding and proceed as with new woods.
2. If they are varnished with closed-pore varnishes, sand deeply and if necessary remove by stripping with chemical or mechanical means and proceed as on new woods.
3. If they are varnished with cellulose or polyurethane varnishes, remove by stripping with chemical or mechanical means and proceed as on new woods.
4. If they are enamelled with synthetic enamels, remove by stripping with chemical or mechanical means, sand down to wood and proceed as on new woods.

Enamelled iron and derivatives:

1. Over paint in good condition, sand to open the pores, checking that adhesion is perfect.
2. On paintwork in bad condition, remove by mechanical or chemical means and proceed as on new base.

Galvanised and light metals:

1. Remove all grease and apply directly.

WAY OF USE

Application Notes

- Stir product thoroughly.
- Only apply on clean surfaces, clean off any dirt by using clean water and detergents.
- Follow guidelines as shown in table below.
- Do not apply product at temperatures below 5° C or any surfaces which have been exposed to sunshine.
- Do not apply when moisture contents it over 80%.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	0-5%
Roller	0-5%
Air-less gun	5-15%
Air-mix gun	5-15%
Aerographic gun	5-15%

CREA ESMALTE LACA SATINADO

Low pressure turbo

5-15%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Metal decoration			
MAX	Crea Imprimación Antioxidante	Crea Esmalte Laca Satinado	Crea Esmalte Laca Satinado
STD	Crea Esmalte Laca Satinado		Crea Esmalte Laca Satinado
Old paintings in bad state			
MAX	Eliminar + Fijador	Crea Esmalte Laca Satinado	Crea Esmalte Laca Satinado
STD	Eliminar + Crea Esmalte Laca Satinado		Crea Esmalte Laca Satinado
Old painting in good state			
MAX	Crea Esmalte Laca Satinado		Crea Esmalte Laca Satinado
STD	Crea Esmalte Laca Satinado		Crea Esmalte Laca Satinado
Wood			
MAX	Crea Selladora	Crea Esmalte Laca Satinado	Crea Esmalte Laca Satinado
STD	Crea Esmalte Laca Satinado		Crea Esmalte Laca Satinado
Iron, Steel			
MAX	Crea Imprimación Antioxidante	Crea Esmalte Laca Satinado	Crea Esmalte Laca Satinado
STD	Crea Imprimación Antioxidante	Crea Esmalte Laca Satinado	Crea Esmalte Laca Satinado
Project			
MAX	Fijador	Crea Esmalte Laca Satinado	Crea Esmalte Laca Satinado
STD	Crea Esmalte Laca Satinado Diluido		Crea Esmalte Laca Satinado
Galvanised and light metals			
MAX	Crea Imprimación Multihaderente	Crea Esmalte Laca Satinado	Crea Esmalte Laca Satinado
STD	Crea Esmalte Laca Satinado		Crea Esmalte Laca Satinado

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

771998

Fecha de Alta

11-09-2014

Versión

6 - 21/06/2017

CREA ESMALTE LACA SATINADO



PACKINGS

0.5 L, 2.5 L