

Fecha de Alta

02-04-2014

Versión

5 - 08/06/2020



FAMILY CREA

LINE TRATAMIENTOS ESPECIALES

DESCRIPTION AND NATURE

Mixture of solvents, like his name indicates, it is suitable for the cleanliness of most of the solvent based paints

USAGES

Indoors/Outdoors

Exotic woods and rich in tannins in general.

Wood

Generic fast-evaporating cleaning solvent

PROPERTIES

High power of cleanliness

Aggressive degreaser

Acts as a cleaner for everyday cleaning purposes

TECHNICAL CHARACTERISTICS

Referencia Color	CREA LIMPIADOR MADERAS
Specific weight	0,81 ± 0,05 kg/l
Solids in volume	0 ± 1
Solids in weight	0 ± 1
Aproximated performance by coat	Depending of product usage

Dry to touch	Median
Colours	Transparent

SURFACE PREPAIRING

New surfaces

Proceed following the paint instructions in which this product is recommended.

Restoring and maintenance

Proceed following the paint instructions in which this product is recommended.

WAY OF USE

Application notes

- As a viscosity regulator:
- Add on top of paint or varnish, in the proportion stated in the specifications sheet of the product to be diluted.
- Slowly stir the previous mix with a spatula until you get a smooth mixture.
- As a tool cleaning solvent:
- Clean tools immediately after use until all varnish and paint has completely disappeared.
- Then wash with soapy water and dry immediately after washing.

Solvent for dilution and cleaning

Way of use	Aproximate dilution
-------------------	----------------------------

Fecha de Alta

02-04-2014

Versión

5 - 08/06/2020

SYSTEM

Procedures depending of surface type

Primer

Intermedium

Finish

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

1 L